



NORTH CAROLINA SHERIFFS' ASSOCIATION

| Name of Dealership | Type of Vehicle | Zone | Base Unit Price |
|--|------------------------|----------------|------------------------|
| <u>G-S - MP8000D (Specification #08)</u> | | | |
| GSP Marketing | 2016 G-S MP8000D | ★Appalachia | \$86,970.02 |
| GSP Marketing | 2016 G-S MP8000D | ★Dogwood | \$86,970.02 |
| GSP Marketing | 2016 G-S MP8000D | ★Cardinal | \$86,970.02 |
| GSP Marketing | 2016 G-S MP8000D | ★Longleaf Pine | \$86,970.02 |



NORTH CAROLINA SHERIFFS' ASSOCIATION

G-S - MP8000D SPECIFICATION #8

2016 G-S MP8000D

Dual - side loading, semi-automated, full eject - This specification describes a truck mounted, hydraulic refuse packer. This machine must be equipped with loading mechanisms on both the curb and street sides of the material receiving hopper near the front of the body. Body must be designed so that optimum load distribution can be achieved when installed on a 25,900-46,000 G.V.W. truck cab and chassis. Body installation shall not require modification to a standard truck chassis forward of the rear suspension. (no drop frame)

ALL ITEMS FACTORY INSTALLED UNLESS OTHERWISE INDICATED

INSTRUCTIONS: Listed above, you will find the model numbers of the vehicles that will be included in this year's contract.

1. BODY CAPACITY

- a. MP8133D - 33YD

2. BODY DIMENSIONS - BODY LENGTH (INCLUDING BUSTLE TAILGATE)

- a. MP8133D - 311"

3. BODY DIMENSIONS - OVERALL HEIGHT ABOVE CHASSIS (LIFT MECHANISM INCLUDED)

- a. MP8133D - 102"

4. BODY DIMENSIONS

- a. Overall height above chassis - MUST NOT EXCEED 112" - (bin in full "up" position) NO EXCEPTIONS ALLOWED
- b. Overall body width with loading buckets down - 102"

5. BODY CONSTRUCTION

- a. The body floor shall be constructed of 1/4" HARDOX 450 steel plate
- b. The body floor shall have 6" x 10.5 lbs/ft structural channel long - members
- c. Body sides shall be curved shell style, ten (10) gauge steel sheet
- d. Body roof shall be curved shell style, ten (10) gauge steel sheet
- e. All external welds shall be continuous

6. TAILGATE CONSTRUCTION

- a. Body tailgate shall be bustle type, top hinged, with heavy-duty hinges and tapered-pin plunger style locks. Pivots and lock pins must have grease fittings
- b. Tailgate shall be equipped with a flow control device to assure smooth, even operation
- c. Tailgate to be constructed from 12 gauge steel sheet and framed with formed steel channel
- d. Gate shall have seal across the bottom and at least 12" up each side to control liquid leakage

7. TAILGATE OPERATION

- a. For greater operational stability and safety the tailgate shall be raised and lowered with two 2 1/2" bore x 28" stroke double acting hydraulic cylinders
- b. All tailgate controls shall be located inside the truck cab within easy reach of the operator's position. I.E. tailgate operation shall not require exit of the cab by the driver. Controls shall be electric/air/hydraulic and spring returned to the "neutral" position
- c. Tailgate to lock and release hydraulically through the use of positive acting, tapered rod, plunger-style locks
- d. Tailgate ajar and lock status warning light and alarm to be installed in the truck cab
- e. Safety prop for tailgate to be included
- f. All exterior welds to be continuous

8. PACKER HOPPER FUNCTION

- a. The receiving hopper shall have 4.8 cubic yards capacity minimum.
- b. Hopper shall act as a receiving chamber for materials dumped by the loading bins
- c. Hopper shall be configured so that both left and right side loading bins can be dumped at the same time without contact or interference with each other

9. PACKER HOPPER CONSTRUCTION

- a. Hopper floor to be constructed of 1/4" HARDOX 450 steel plate
- b. Hopper side walls to be 1/4" HARDOX 450 steel plate
- c. Hopper shall include 1/4" Hardox 450 liner, extends 18" past packer travel

10. COMPACTOR FUNCTION

- a. Compactor is to move the material dumped by the loading bins from the receiving hopper into the body chamber. Also, compactor is to compress the loaded material to such an extent that the vehicle is loaded to it's recommended capacity

11. COMPACTOR OPERATION

- a. Compactor to be powered by one (1), 6" bore x 84" stroke, single section, dual acting hydraulic cylinder. (13 and 16 yard bodies One 5" bore x 60" stroke cylinder)
- b. Packer cycle shall be 42 seconds @1200 R.P.M.
- c. Unit to be equipped with a "near-loaded" warning alarm to alert operator that body is approaching it's maximum capacity
- d. Compactor stroke shall be automatically reversible through the use of high quality automotive grade switches sensitive to both position and pressure
- e. Compactor shall have "on-demand" style controls with locations in the truck cab and convenient to each loading bin
- f. Compactor shall displace 2.6 cubic yards/cycle minimum
- g. When fully extended, compactor must penetrate the body by 18" minimum. This aids compaction of the material and reduces fallback into the loading hopper

12. COMPACTOR CONSTRUCTION

- a. The compactor shall be constructed of engineered steel sections and fully tested using state-of-the-art Finite Stress Analysis technology
- b. Both the "T" track beam and compactor guide shoes must be made of HARDOX 450 steel plate
- c. Compactor to be guided by a floor mounted "T" track beam

13. LOADING DEVICE FUNCTION

- a. The loading device must provide top loading of materials into the receiving hopper
- b. The loading height of the bin shall be approximately 40" (may vary with tire and frame options)
- c. Each lifting mechanism must be operated by one (1), 4" bore x 16" stroke, hydraulic cylinder with 1 1/2" fluid cushions in both the rod and base ends
- d. Lift cycle time shall be approximately 10 seconds at engine idle
- e. When in the full dump position, the bin dump angle must be 52 degrees minimum, measured from a horizontal line parallel to the ground
- f. The loading bins must tilt 5 degrees during the lift cycle to control spillage
- g. The loading bins must have "CHIP-GUARD" coating on the inside surface for easy clean-out during the dump cycle
- h. The body to bin gap, (space between the loading bin and body sides) must not exceed two (2) inches during the dump cycle. This prevents overhead spillage and reduces the need for clean-up
- i. Bins shall be track guided by roller bearing type steel rollers and stabilized by two lift arms, one at each end
- j. Loading bin lifting mechanism operation must be smooth and non-binding, regardless of uneven bin loading

- k. Loading bin lifting capacity must be 2500 lbs. minimum with a 2 to 1 design safety factor
- l. Loading bin volume shall be one and one-half (1 1/2) cubic yard each
- m. Top opening of loading bins shall measure 72" x 24" minimum. Smaller openings are not acceptable

14. LOADING DEVICE CONSTRUCTION

- a. Loading bin lifting arms must be constructed of solid, high tensile steel plate, minimum allowable section modulus for loading bin lift arms shall be 3.0 cubic inches. Tubular load lifting components are not acceptable
- b. All loading bin lift arm connecting pins shall be 1.25" minimum diameter with spring steel bushings and grease fittings
- c. Loading bins shall be constructed of 12 gauge COR-TEN steel sheet supported by a tubular steel frame. Ends of bins shall be 10 gauge COR-TEN steel sheet

15. LOADING DEVICE CONTROLS

- a. Controls for each loading mechanism shall be located immediately behind the chassis cab and convenient for operator access
- b. The lift control valve shall be a three (3) position air directional valve

16. BODY UNLOADING FUNCTION

- a. Controls to be mounted convenient to operator's in-cab driving location
- b. Ejector operation shall be sequenced so that panel will "extend" only when packer panel is in full "extend" position and tailgate is fully "up"
- c. Ejector panel to be operated by two (2), 3" bore x 104" stroke, single section, double-acting hydraulic cylinders
- d. Body payload to be offloaded by hydraulically powered horizontal ejection

17. BODY UNLOADING CONSTRUCTION

- a. Floor level wear pads must be HARDOX 450
- b. Panel guide/cylinder enclosure tube shall be 5" x 7" x 3/16" structural steel tube equipped with HARDOX 450 steel wear strips
- c. Panel guide tracks to be formed 3/16" steel plate
- d. Ejector panel to have a structural steel tubular frame

18. HYDRAULICS PUMP

- a. All body and lift functions shall be powered by a single-section gear type pump. This pump shall be powered by a transmission mounted "hot shift" power take off

19. HYDRAULICS CONTROL VALVE

- a. The body and lift functions shall be controlled by a single stack type air activated directional hydraulic valve. All controls for the body and lift shall be air/hydraulic. This directional control valve shall be equipped with a reliable system pressure protection device. The maximum system operating pressure shall be 2500 P.S.I

20. HYDRAULIC RESERVOIR

- a. The body shall be equipped with a hydraulic reservoir with a minimum capacity of thirty (30) gallons. This reservoir shall be equipped with a fill cap, breather, fluid level indicator and temperature gauge

21. HYDRAULIC FILTRATION AND SERVICE (SYSTEM CLEANLINESS AND PROTECTION AGAINST CONTAMINATION SHALL BE ACCOMPLISHED THROUGH THE USE OF THE FOLLOWING DEVICES)

- a. Suction Strainer - A 100-mesh oil strainer must be installed in the hydraulic system suction line. This strainer must be serviceable without draining the system reservoir
- b. In-Line Shutoff - For ease of service the suction line shall be equipped with a shutoff valve plumbed adjacent to the reservoir
- c. High Pressure Filter - All oil shall be routed through a 10 micron pressure line filter. This filter shall be installed between the hydraulic pump and the body control valve and properly sized so that 100% of the flow is filtered under normal operating conditions without bypass. Filter must be located so that all periodic service can be performed from ground level without the need for ladders or work-stand

22. HYDRAULICS PLUMBING

- a. All body and lift plumbing not requiring flexibility to complete its function must be constructed of seamless steel hydraulic tubing correctly sized for each operation. Plumbing requiring hoses shall be routed in such a way as to prevent rubbing, chafing and undue bending

23. IN-CAB CONTROLS (THE FOLLOWING CONTROLS MUST BE MOUNTED INSIDE THE TRUCK CAB FOR SAFE AND CONVENIENT OPERATION)

- a. Hydraulic system on/off switch
- b. Body tailgate control
- c. Body ejector control
- d. Work light and strobe light switches

24. LIGHTS

- a. Standard lights shall be supplied in accordance with FMVSS#108
- b. All body lights must be TRUCKLITE Model "SUPER 44" L.E.D. with SERIES 50 wiring harness
- c. Both street side and curbside loading locations must have work lights

25. ACCESSORIES

- a. Federal under-ride bumper shall be installed
- b. Tailgate safety prop shall be provided
- c. Body "up" and tailgate "unlock" alarm shall be provided
- d. Back up alarm shall be provided
- e. Both body and hopper shall have access doors on each side for cleaning behind the packer and ejector panels. Doors must be sealed when closed

26. PAINTING PROCEDURES

- a. The body and lift shall be free of all weld slag, dirt and grease and be prepared prior to painting in accordance with the paint manufacturers specifications
- b. Body and loading mechanism shall receive at least one coat of primer and one finish coat of polyurethane enamel. Primer shall be approved for use with the finish coat material

27. WARRANTY

- a. A minimum two-year warranty against manufacturing defects shall be provided by the manufacturer



NORTH CAROLINA SHERIFFS' ASSOCIATION

G-S - MP8000D SPECIFICATION #8

2016 G-S MP8000D

The G-S MP8000D purchased through this contract comes with all the standard equipment as specified by the manufacturer for this model and NCSA's base vehicle specification(s) requirements which are included and made a part of this contract's vehicle base price as awarded by specification by zone.

| | | | | |
|-------------|-------------|-------------|-------------|----------------|
| ZONE: | ★Appalachia | ★Dogwood | ★Cardinal | ★Longleaf Pine |
| BASE PRICE: | \$86,970.02 | \$86,970.02 | \$86,970.02 | \$86,970.02 |

While the North Carolina Sheriffs' Association has attempted to identify and include those equipment items most often requested by participating agencies for full size vehicles, we realize equipment needs and preferences are going to vary from agency to agency. In an effort to incorporate flexibility into our program, we have created specific add/delete options which allow the purchaser to tailor the vehicle to their particular wants or needs.

The following equipment delete and add options and their related cost are provided here to assist you in approximating the total cost of the type vehicle(s) you wish to order through this program. Simply deduct the cost of any of the following equipment items you wish deleted from the base unit cost and/or add the cost of any equipment items you wish added to the base unit cost to determine the approximate cost of the type vehicle(s) you wish to order.

NOTE: An official listing of all add/delete options and their prices should be obtained from the appropriate dealer in your zone when preparing your order. Additional add/delete options other than those listed here may be available through the dealers, however, those listed here must be honored by the dealers in your zone at the stated prices.

| | | | | |
|--------------------|---------------|---------------|---------------|-----------------|
| VEHICLE: | MP8000D | | | |
| DEALER: | GSP Marketing | GSP Marketing | GSP Marketing | GSP Marketing |
| ZONE: | ★ Appalachia | ★ Dogwood | ★ Cardinal | ★ Longleaf Pine |
| BASE PRICE: | \$86,970.02 | \$86,970.02 | \$86,970.02 | \$86,970.02 |

| Order Code | Add Options | All Zones |
|-------------------------------------|---|--------------------------|
| Cart tipper ¹ | Dumping attachment for 30-100 gallon containers. Semi-automated container attachments must be equipped with positive lock, automatic container latches. These latches must be linkage actuated by the lower bin lift arm and must require no action by the operator other than bin control lever operation. In order to prevent possible container damage, the container latches must automatically engage the container lower bar after the container is well clear of the ground or curb on the bin "up" cycle and automatically release well before the container reaches the ground or curb on the bin "down" cycle. Attachment of semi-automated carts to the container attachment shall not require tipping of the container or opening of the container lid for proper engagement <i>Single cart tipper attachment ¹</i> | \$653.54 ¹ |
| Peterson Strobe ¹ | Strobe lights (Smart strobe, 4 on rear and 2 on front of body) | \$1,933.56 ¹ |
| Hyd monitor w/shutdown ¹ | Hydraulic filter monitor with shut down | \$533.82 ¹ |
| | Extra set of rocker switches for controls | NA |
| Single camera ¹ | Camera system - Single Camera | \$1,813.02 ¹ |
| Dual camera ¹ | Camera system - Dual camera w/quad monitor | \$2,321.42 ¹ |
| Triple camera ¹ | Camera system - Triple camera w/quad monitor | \$2,827.36 ¹ |
| Ft hopper cover ¹ | Full hopper cover (Front manually activated) | \$1,100.00 ¹ |
| Fold out bucket ¹ | Fold out buckets <i>Per side ¹</i> | \$634.68 ¹ |
| Delivery ¹ | Truck delivery <i>Per mile ¹</i> | \$2.50 ¹ |
| 4 end dump ¹ | 4 yard end dump bed | \$14,800.00 ¹ |
| MP8113D ¹ | MP8113D - 13YD | \$60,793.98 ¹ |
| MP8116D ¹ | MP8116D - 16YD | \$62,700.48 ¹ |
| MP8120XD60 ¹ | MP8120XD 60" Hopper - 20YD | \$72,676.60 ¹ |
| MP8120XD84 ¹ | MP8120XD 84" Hopper - 20YD | \$73,526.12 ¹ |
| MP8127D ¹ | MP8127D - 27YD | \$80,217.32 ¹ |
| MP8129D ¹ | MP8129D - 29YD | \$82,565.80 ¹ |
| MP8131D ¹ | MP8131D - 31YD | \$84,624.82 ¹ |
| MP8135D ¹ | MP8135D - 35YD | \$89,104.48 ¹ |
| MP8137D ¹ | MP8137D - 37YD | \$91,449.68 ¹ |
| | MP8113D - 185" | NA |
| | MP8116D - 185" | NA |
| | MP8120XD 60" Hopper - 209" | NA |
| | MP8120XD 84" Hopper - 233" | NA |

| | | | | |
|--------------------|---------------|---------------|---------------|-----------------|
| VEHICLE: | MP8000D | | | |
| DEALER: | GSP Marketing | GSP Marketing | GSP Marketing | GSP Marketing |
| ZONE: | ★ Appalachia | ★ Dogwood | ★ Cardinal | ★ Longleaf Pine |
| BASE PRICE: | \$86,970.02 | \$86,970.02 | \$86,970.02 | \$86,970.02 |

| | |
|----------------------------|----|
| MP8127D - 277" | NA |
| MP8129D - 287" | NA |
| MP8131D - 301" | NA |
| MP8135D - 325" | NA |
| MP8137D - 335" | NA |
| MP8113D - 84" | NA |
| MP8116D - 94" | NA |
| MP8120XD 60" Hopper - 102" | NA |
| MP8120XD 84" Hopper - 102" | NA |
| MP8127D - 102" | NA |
| MP8129D - 102" | NA |
| MP8131D - 102" | NA |
| MP8135D - 102" | NA |
| MP8137D - 102" | NA |