



NORTH CAROLINA SHERIFFS' ASSOCIATION

Name of Dealership	Type of Vehicle	Zone	Base Unit Price
<u>MACK GU812 – (4X2 – REAR LOADER, SIDE LOADER, ROLL-OFF, KNUCKLEBOOM, HOOK LIFT) (Specification #32)</u>			
Transource, Inc.	2017 Mack GU812	★Appalachia	\$86,830.39
Transource, Inc.	2017 Mack GU812	★Dogwood	\$86,830.39
Transource, Inc.	2017 Mack GU812	★Cardinal	\$86,830.39
Transource, Inc.	2017 Mack GU812	★Longleaf Pine	\$86,830.39



NORTH CAROLINA SHERIFFS' ASSOCIATION

MACK GU812 – (4X2 – REAR LOADER, SIDE LOADER, ROLL-OFF, KNUCKLEBOOM, HOOK LIFT) SPECIFICATION #32

2017 Mack GU812

ALL ITEMS FACTORY INSTALLED UNLESS OTHERWISE INDICATED

INSTRUCTIONS: Listed above, you will find the model numbers of the vehicles that will be included in this year's contract.

1. ENGINE

- a. Engine Package - MP7-325M Mack 325 @ 1500-1900 RPM (Peak) 2100 RPM (governed) US'14 (1200 lb-ft)
- b. Turbo Family for 2017 - Turbo single stage
- c. Engine Governor Type Min-Max

2. TRANSMISSION

- a. Transmission - Y310 10 SP-Mack
- b. Without transmission electronics

3. EXHAUST/EMISSIONS

- a. CARB 2008 Idle Regulation - Idle emission certification, CARB 08 (with decal located on lower LH corner/driver door)
- b. DPF Cover - DPF Cover, painted steel
- c. DPF Diesel Particulate Filter - Cleartech HHS DPF RH side under cab w.SCR frame MTD RH side - US10
- d. Exhaust - No muffler, single (R/S) vertical straight EXH stack turned out end, outboard
- e. Exhaust Heat Shield Type - Exhaust heat shield type, basic
- f. Exhaust Stack Height - Exhaust stack 3.55 metre, height over ground (11'6")
- g. Exhaust System Material Finish - Standard exhaust system material finishing
- h. Def Tank - 45L/22" Dia semi tank left side frame mtd
- i. Def Tank Cover - Def tank cover, painted finish
- j. Exhaust Aftertreatment System - Selective catalyst reduction + diesel part. filter ceramic
- k. Emission on Board Diag. Control - Emission OBD. display only, USA2016

4. ENGINE EQUIPMENT

- a. Air Cleaner - 11" single element Donaldson
- b. Air Intake Source - Air intake source, hood outside
- c. Bug Screen - w/o bug screen / winter front
- d. Air Compressor - Meritor/Wabco 318 (18.7 CFM)
- e. Primary Fuel Filter Position (CA) - Standard fuel filter position
- f. Alternator - 12V130A Delco 24SI (130 AMP)
- g. Batteries - 3-12V Mack M/F 31 650 CCA Threaded stud type
- h. Cooling Performance - Narrow radiator with length 4 (60 DM2), 41 DEG C ATB, cooling capacity
- i. Coolant Protection - To -34 deg F
- j. Coolant Filter/Conditioner - with filter/conditioner
- k. Fan Drive - BEHR fan and electronic modulating viscous fan drive
- l. Engine Brake - w/o Engine Brake
- m. Fuel - Water Separator - Mack integral includes manual drain
- n. Fuel Equipment Water Heater (CA) - Without fuel heater equipment

- o. Battery Box Mounting - RH behind SCR - US10
- p. Battery Box Cover - Basic battery box cover
- q. Battery Disconnect Switch - W/O battery disconnect switch
- r. Emergency Start Studs - Without emergency start studs
- s. Hoses - Radiator/Heater - mack brand EPDM radiator and heater hoses
- t. Starter - 12V standard starter Delco 39MTHD
- u. Oil Pan - Oil pan steel
- v. Tether Dev. Package, Caps and Covers - Without tether device package for caps and covers
- w. Engine Block Heater - without engine block heater
- x. Engine Oil Pan Heater - Without engine oil pan heater
- y. Engine Starting Aid - Without starting aid
- a`. Breather Filter - Without breather filter
- aa. Engine Oil Drain Kit - Without engine oil drain kit
- ab. Battery Shock Pads - Without battery shock pads
- ac. Smart Idle Elevated Idle RPM Time - Increase 10 minute maximum time

5. CLUTCH/TRANSMISSION EQUIPMENT

- a. Clutch - Eaton advantage EZ-Pedal 9 spring, 2 platye 15.5" ceramic 6 paddles, manual adjust
- b. Driveline - Main - meritor 18 MXL "Xtended Lube"
- c. Clutch Actuation System - Clutch actuation system, mechanical, cable
- d. Lubricants, Transmission - Petroleum oil in transmission
- e. Clutch Pedal Pad - Clutch pedal pad, rubber
- f. Transmission Oil Cooler - Without oil cooler
- g. Transmission Dust Proofing - Without transmission dust proofing
- h. Prop Shaft Bearing Guard - Without prop shaft bearing guard
- i. Propeller Shaft Main, Universal Jnt. - Propeller shaft main, universal joint half-round type
- j. Hill Start Assist - Without hill start assist
- k. Bell Housing - Aluminum bell housing
- l. Clutch Brake - Clutch brake, one piece
- m. Clutch Lube Line - Without lubeline between release bearing and bell housing
- n. Retarder - Without retarder
- o. Transmission Torque Converter - W/O transmission torque converter
- p. Transmission Adaptation Ring - W/O transmission adaptation ring
- q. Gear Shift Lever - Gear Shifting, Basic
- r. Engine Start Condition - Without engine start condition
- s. Trans Shift Mode Points - W/o trans shift mode points
- t. Transmission Protection - Without transmission protection
- u. Econo Roll - Econo roll disable M-drive (required for all other transmissions)
- v. mDrive Mackcellerator - Without transmission kick-down mode

6. FRONT AXLE EQUIPMENT

- a. Front Axle - FXL 12 12,000 Lb - Mack 5400 KG (N/a with lift axles)
- b. Springs - Front - 12,000 Lb taperleaf 5400 kg (2-leaf spring)
- c. Front Axle Brakes - Meritor "S" Cam 16.5 x 5" Q Plus brakes
- d. Brake, Front - Cast iron brakedrum, front axle
- e. Front Axle Brake Dust Shield - Front brakes without dust shields
- f. Front Brake Chamber MFG. - Front brake chamber manufacturer, MGM
- g. Front Brake ADJ. Manufacture - Front brake adjustment, automatic Haldex
- h. Front Spring Bias - Without front spring bias (equal stiffness L/R)
- i. Brake Lining Material Front - Brake lining material, front, fed mogul abex 931-162/R301
- j. Hub Material, Front - Basic material hub (steel/cast iron), front
- k. Hub Oil Seal, Front - FAG Schaeffler, front hub oil seal
- l. Spindle Nuts, Front - Basic (no option) spindle nuts, front
- m. Shock Absorber, Front - With shock absorber, front
- n. Steering - TAS-66 TRW Power (integral)
- o. Lubricants, Front Axle - Petroleum oil in front axle
- p. Front Brake Chamber Size - Front brake chamber 20sq inches (service)
- q. Brake Regulation - Brake regulation, stopping distance 94M (310ft)

7. REAR AXLE EQUIPMENT

- a. Rear Axle Single - RA23R 23000 Lb-Mack 10400 KG
- b. Rear Axle Casing Width - Rear axle casing width, standard
- c. Lube Pump, Rear Axle - Without lube pump, rear axle
- d. Carrier - Rear Axle - CRD151
- e. Rear Axle Ratio - Ratio 3.11, rear axle
- f. Rear Suspension - Single - 23000 lb multileaf 10400kg no anti-sway
- g. Springs - Anti-Sway - W/O anti-sway
- h. Suspension Leveling Device - W/O Susp. leveling device
 - i. Air Suspension Dump Warning - W/O air suspension dump warning
 - j. Rear Shock Absorber - W/O shock absorber, rear
- k. Transverse Torque Rods, R Susp. - Without rear suspension transverse torque rod
 - l. Brakes, Rear - Meritor - CAM 16.5x7 Q Plus
- m. Brake Drums/Rotors, Rear - Cast iron brake drums
- n. Rear Brake ADJ Manufacture - Rear brake adjustment, automatic haldex
- o. Rear Brake Chamber Size - Rear brake chamber 30/30 sq. inches (service/emergency)
- p. Drive Axle Brake Dust Shield - Rear drive brakes without dustshields
- q. Brake Lining Material Drive - iron preset hub, drive, w/ integrated spindle nut
- r. Hub Material, Drive - Iron preset hub, drive, w/ integrated spindle nut
- s. Hub Oil Seal, Drive - Premium hub oil seal, drive
- t. Power Divider Lockout - W/O power divider
- u. Lubricants, Rear Axle - Petroleum oil in rear axle
- v. Spring Brake Chambers, Vendor - MGM model TR-T; tamper-resistant brake chambers
- w. Traction Differential - W/O intr-WHL/differential options
- x. Spindle Nuts, Main Axle - Spindle nuts, main axle, integrated
- y. ABS Sensor and Modulator - ABS 4 sensors and 4 modulators (front and rear axles)
- a`. Anti-Lock Brake System - Bendix KB (Eaton/Bosch), ABS
- aa. Brake Valve Version - Brake valve version, USA-Bendix, where possible
- ab. Traction Control Disable - W/O traction control disable

8. PUSHER/TAG AXLE EQUIPMENT

- a. Option Center Support - W/O option center support

9. FRAME EQUIPMENT/FUEL TANKS

- a. Wheelbase - 215"
- b. AF (Overhang) - 71"
- c. Frame Rails - Steel - 300MM x 90MM x 8MM -- (11.81" x 3.54" x 0.31")
- d. Frame Inner Liner - Without liner
- e. Frame Outer Liner (CA) - Without frame outer liner
- f. Front Frame Ext. (bolted on) - 155mm, front frame extension, bolted on (6")
- g. Front Frame Length - Front frame length - 1285MM
- h. Crossmembers - Boc and intermediate (s) = steel HD back to back channel
 - i. Frame Rail Free Space - W/O frame rail clearance
 - j. Fuel Tank Polish Option - W/O fuel tank polish option
- k. Rear Crossmember Options - Rear crossmember, straight frame end (basic)
 - l. Rear Frame Treatment - Straight cut treatment, rear frame
- m. Mudflap Hangers, Rear Axle - Without mudflap hangers, rear axle
- n. Mudflap, Front Axle - Without mudflap, front axle
- o. Front Bumper - Bumper, steel painted extended, including stone guard
- p. Guard, Under Engine BAYT - Without guard
- q. Aux. Crossm. in Rear Overhang - Without auxilliary crossmember in rear overhang
- r. Towing Device, Front - Without towing device, front
- s. Towing Coupling - Without towing coupling
- t. Towing Device, Rear - Without towing devices, rear
- u. Fuel Tank, LH - 50 gallon (190 liters) 22" (560mm)
- v. Fuel Level Sender Unit, Liquid - Basic fuel level sender mounted on LH tank
- w. Fuel Tank, RH - Omit RH fuel tank
- x. Toolbox Chassis - W/O toolbox chassis
- y. Filler Neck Screens - W/O filler neck screen w/o sump
- a`. Fuel Line Options Liquid - Fuel line option, single
- aa. Fuel Tank Cap - Non-lockable fuel tank cap
- ab. Steps (bright) Fuel Tank, W/O bright finish steps and straps package

- ac. Fuel Fill System, Liquid - Fuel fill system, basic
- ad. Quarter Fenders - W/O rear axle fenders
- ae. Isolate Tank from Fuel System - W/O isolated tank

10. AIR/BRAKE

- a. Airtank Material - Steel airtank
- b. Airtank Drain Valve - petcock drain valve, on brake sys tanks
- c. Air Dryer, Manufacturer - Wabco Air Dr., 1200 Up W/ T Cut Off Valve, W Coalesec oil filter
- d. Air Dryer Position (CA) - Air dryer position standard
- e. Park Brake Alarm (CA) - Without park brake alarm
- f. Parking Brake Valve - Parking brake valve, 1 yellow knob, all parking
- g. Relocate Air Reservoirs - W/O relocated air reservoirs
- h. Auxiliary Airtank - W/O aux. airtank

11. ELECTRICAL

- a. Auxiliary Spotlight (CA) - Without auxiliary spotlight
- b. Auxiliary Pneumatic Outlet Cab - W/O auxiliary pneumatic outlet, in cab
- c. Chassis Wiring Harness Casing - Chassis wiring harness casing, basic
- d. Parking Brake Lighting - W/O parking brake lighting
- e. Dash Panel Box - Dash panel clip and cell phone holder
- f. Back-Up Alarm - W/O back up alarm
- g. Aux. Fog Lamp - W/O fog lamp
- h. Auxiliary Lamps - W/O auxiliary lamps
- i. Tail Lamps - Tail lamp, multipurpose
- j. Dash Mounted Switches - W/O aux. switch wiring
- k. Marker/Directional Signal - W/O marker/directional signal option
- l. Daytime Running Lights - DRL when engine running, park brake off
- m. Warning Lamp - W/O warning lamp

12. TRAILER CONNECTIONS

- a. Trailer Glad Hand Couplings - W/O brake connection
- b. Fifth Wheel Angle Thickness - W/O fifth wheel angle thickness
- c. Fifth Wheel Angle Material (CA) - W/O fifth wheel angles
- d. Trailer Brake Valve - W/O trailer brake valve
- e. Trailer Connection Position - W/O trailer connection position
- f. Electrical Recept, Aux. Power - W/O electrical recept. aux power
- g. Trailer Electrical Recept. - W/O trailer electrical recept
- h. Trailer Hookup Light - W/O cab mtd trailer hookup lamp

13. PTO/SPECIALTY EQUIPMENT

- a. Hydraulic Pump - W/O hydraulic pump
- b. Front Body Attachment - W/O front body attachment
- c. Frame Modifications - No frame modifications provided
- d. Certified Weight - Customer guaranteed weight, must be certified weight
- e. Rust Protection Additional (CA) - W/O transp. rust protection
- f. Aux. Transmission Cooler (CA) - W/O auxiliary transmission cooler
- g. Rear Engine PTO - W/O rear engine PTO
- h. PTO Trans Neutral Control Check - W/O PTO transmission neutral control check
- i. Power Take Off Control - W/O power take off control
- j. Crankshaft Adapter - W/O front end PTO drive
- k. Bulk Unloading Adaptation - W/O bulk unloading adaptation
- l. Body Builder Interface - Body link3 W cab pass thru
- m. Unique Decals Machine DirectIV (CA) - W/O decals
- n. PTO Trans Side, Free Space - W/O PTO transmission side, free space
- o. PTO, Rear Mounted - W/O Rear MTD PTO - (non-M-drive)

14. CAB (A THRU G)

- a. Air Conditioning/Heater - Blend Air HVAC
- b. Air Intake Grille, Finish - Air intake grille, gray

- c. Air Restriction Indicator - W/O air restriction indicator
- d. Antenna, Satellite - W/O satellite antenna
- e. Ashtray
- f. Audio Shutoff - W/O automatic audio shutoff
- g. Audio Speaker Location - Speaker location, behind doors, middle high side panel
- h. Bug Deflector, Windscreen - W/O bug deflector
- i. Cab Aux. Fan - W/O cab aux. fan
- j. Cab Instep Version - Cab step version basic
- k. Cab Glass - Tinted windshield, side windows, and rear window
- l. Cab Peep Window - W/O cab peep window
- m. Cigar Lighter
- n. Dash Indicator, Lamp Body Out of POS - W/O dash indicator lamp
- o. Dome Lamp, Interior - Dome lamp, interior, 2 each side, switches included
- p. Door Storage Compartment - W/O door storage compartment
- q. Front Wheel Opening - Basic front wheel opening
- r. Fire Extinguisher - W/O fire extinguisher
- s. Floor Covering - Polyurethane floor mat
- t. Gauge, Ambient Temperature - W/O gauge, ambient temperature
- u. Time Counter (CA) - W/O time counter
- v. Gauge, Odometer - No hubodometer provided
- w. Gauge, Oil Temp., Rear Axle - W/O axle oil temp. gauge
- x. Gauges, Packages - Std. package + engine oil temperature, transmission oil temp and exh. pyrometer
- y. Gauges, Unit of Measure - U.S. Units (predominant)
- a`. Grab Handles - BF exterior cab grab handles, BL grab handle RH interior windshield post
- aa. Grille - Silver painted grille W/O grille surround

15. CAB (H THRU R)

- a. Headliner Material - Headliner, vinyl
- b. Hood Hatch - W/O hood hatch
- c. Hood Latch Finish - Hood latch finish, black
- d. Horn, Air - W/O air horn
- e. Horn, Electrical - 1 single electric horn single tone
- f. Instrument Cluster Display - Co-pilot DRVR disp enhanved 4.5" diag. LCD display w/4 button stalk control, diag. disp. basic
- g. Dashboard - Basic dashboard
- h. Interior Trim Levels - Purebred sandstone
- i. Keyed Alike Chassis - All chassis keyed at random - 2 keys
- j. Door Opening Options - Door opening option, manual
- k. Mirrors, Convex Type Cab Doors - Bright finish (LH and RH) 8.0" dia.
- l. Mirror, Convex Hood and Fender - W/O convex hood mirrors
- m. Mirrors, Exterior - Bulldog - BR Fin
- n. Mirrors Heated Timeout (CA) - W/O heated mirror timeout
- o. Mirrors, Proximity - W/O proximity mirror
- p. Forward Overhead Storage - Forward overhead storage, 2 STG compmnt. w/net, 1 radio shelf center
- q. Personalized Name Plate - W/O personalized name plate
- r. Cab Guard, Front - W/O cab guard
- s. Audio Accommodation - W/O radio or radio accommodation package
- t. Antenna, Radio - W/O antenna, radio
- u. Antenna CB Radio, W/O antenna, CB radio
- v. Power Leads - Power Lead, 5 way type, headliner MTD
- w. Communication Radio - W/O communication radio
- x. Com. Radio Prep Kit - CB mounting, overhead comp., mount plate, removable
- y. Rear Cab Suspension- Rear cab suspension, air
- a`. Auxiliary Rear Window - With auxiliary rear window, fixed
- aa. Reflector Kit - W/O reflector kit option
- ab. Roof Hatch or Cooler - W/O roof hatch
- ac. Roof Marker Light - Roof light, non specified manufacturer, curved model
- ad. Rear Wall Storage Compartment - W/O rear wall storage compartment

16. CAB (S THRU Z)

- a. Seat, Drivers - Air Bostrom Talladega 915 (mid black)

- b. Seat, Passenger - Fixed Mack (mid black)
- c. Seat Armrest - Seat armrest single, driver (driver seat only)
- d. Seat Belt(s) - Lap and Shoulder (both seats) to be orange in color
- e. Seat Belt Reminder (CA) - W/O seat belt reminder
- f. Seat Covering - All vinyl, cab interior dependent color, driver and rider seats
- g. Seat Support, Dust Cover - W/O seat support, dust cover
- h. Ignition Type - Ignition type, key
 - i. Steering Wheel - 2 spoke urethane grip, charcoal spokes, W/O switches
 - j. Sun Visor, Interior, Front - Internal sun visor front, basic (no mirror) both sides
 - k. Sun Visor, Exterior - W/O exterior sun visor
 - l. Turn Signals - Non cancelling turn signal
- m. Washing Reservoir Position - Washer reservoir basic position
- n. Window Controls - Roll-Up LH and RH crank operated
- o. Windshield Type - Split windscreen
- p. Windshield Wipers - Two speed electric motor w/intermittent feature
- q. Work Lights - Chassis Mounted - W/O work light, chassis mounted

17. AERODYNAMIC DEVICES

- a. Roof Fairing/Side Shields - W/O provisions for aero aids

18. WHEELS AND TIRES

- a. Tires Brand/Type Front - 11R 22.5 G Bridgestone R268 Ecopia (total for Qty = 2)
- b. Tire Speed Limit - Tire speed limit basic
- c. Wheels, Front - 22.5 x 8.25 STL disc 11.25b.c. Accuride hub piloted 10-hole 2 hand hole heavy duty 28828 (total for qty.=2)
- d. Wheel Finishing, Front - W/O wheel finishing front
- e. Front Axle Tire and Wheel Quantity - Two front tires and wheels
- f. Tires Brand/Type, Rear - 11R 22.5 H Bridgestone R 283A Ecopia (total for qty = 4)
- g. Wheels, Rear - 22.5 x 8.25 STL Disc 11.25 BC Accuride Accu-Lite 10-hole HP 5 hand holes p/n 50487 (total for qty = 4)
- h. Rear Wheel Rim Clamp - W/O rear wheel rim clamp
 - i. Rear Disc Wheel: Polish - W/O RR disc whl bright finish
 - j. Rear Axle Tire and Wheel Quantity - Four rear axle tires and wheels
- k. Wheel Studs (CA) - Wheel studs basic length
 - l. Hub/Wheel Isolator, Front - W/O hub/wheel isolator, front
- m. Hub/Wheel Isolator, Drive - W/O hub/wheel isolator, drive
- n. Wheel Nut and Finish Front - Wheel nut and finish basic, front
- o. Wheel Nut Finish, Rear (CA) - Wheel nut basic finish , rear
- p. Tire Inflation Valve - Tire Inflation valve, standard
- q. Spare Wheel - W/O spare wheel
- r. Spare Wheel Carrier, POS - W/O spare wheel carrier
- s. Hydraulic Jack - W/O hydraulic jack

19. PAINT

- a. Paint Type - Solid paint
- b. Paint Color, Area A - Mack white 08282PP; P9188
- c. Paint/Vinyl Striping - Cab Exterior - Single color without design
- d. Paint Color Area B - W/O area b paint color
- e. Paint Color Area C - W/O area c paint color
- f. Paint, Cab Paint System - Poly through coat W/O clear coat
- g. Paint, Chassis Running Gear - Mack Black P3036
- h. Paint, Bumper - Paint bumper same color as chassis running gear
 - i. Paint, Fuel Tank - Paint fuel tank same color as chassis running gear
 - j. Fuel Tank Paint Process Code - Fuel tank paint process, same as chassis running gear
- k. Front Wheel Paint - Front wheel powder coat, white
 - l. Drive Wheel Paint - Drive wheel powder coat, white
- m. Paint: Disc Wheels, Front - W/O paint
- n. Paint: Disc Wheels, Rear - W/O paint
- o. Paint: Demount Rims, Front - W/O paint
- p. Paint: Demount Rims, Rear - W/O paint

- q. Paint: Spoke Wheels, Front - W/O optional spoke wheel paint
- r. Paint: Spoke Wheels, Rear - W/O optional spoke wheel paint
- s. Paint: Hubs and Drums, Front - Same as chassis running gear
- t. Paint: Hubs and Drums, Rear - Same as chassis running gear

20. APPLICATION PACKAGES - MACK PACKAGE RAWHIDE

- a. Without Mack rawhide package

21. APPLICATION PACKAGES - MHD-AF CONFIGURATION PACKAGE

- a. W/O MHD configuration package

22. APPLICATION PACKAGES - GRANITE AB CONFIGURATION PACKAGE

- a. W/O granite AB configuration package

23. APPLICATION PACKAGES - SPECIAL SALES PACKAGE

- a. Without Special Sales Package



NORTH CAROLINA SHERIFFS' ASSOCIATION

MACK GU812 – (4X2 – REAR LOADER, SIDE LOADER, ROLL-OFF, KNUCKLEBOOM, HOOK LIFT) SPECIFICATION #32

2017 Mack GU812

The Mack GU812 purchased through this contract comes with all the standard equipment as specified by the manufacturer for this model and NCSA's base vehicle specification(s) requirements which are included and made a part of this contract's vehicle base price as awarded by specification by zone.

ZONE:	★Appalachia	★Dogwood	★Cardinal	★Longleaf Pine
BASE PRICE:	\$86,830.39	\$86,830.39	\$86,830.39	\$86,830.39

While the North Carolina Sheriffs' Association has attempted to identify and include those equipment items most often requested by participating agencies for full size vehicles, we realize equipment needs and preferences are going to vary from agency to agency. In an effort to incorporate flexibility into our program, we have created specific add/delete options which allow the purchaser to tailor the vehicle to their particular wants or needs.

The following equipment delete and add options and their related cost are provided here to assist you in approximating the total cost of the type vehicle(s) you wish to order through this program. Simply deduct the cost of any of the following equipment items you wish deleted from the base unit cost and/or add the cost of any equipment items you wish added to the base unit cost to determine the approximate cost of the type vehicle(s) you wish to order.

NOTE: An official listing of all add/delete options and their prices should be obtained from the appropriate dealer in your zone when preparing your order. Additional add/delete options other than those listed here may be available through the dealers, however, those listed here must be honored by the dealers in your zone at the stated prices.

VEHICLE:	GU812			
DEALER:	Transource, Inc.	Transource, Inc.	Transource, Inc.	Transource, Inc.
ZONE:	★ Appalachia	★ Dogwood	★ Cardinal	★ Longleaf Pine
BASE PRICE:	\$86,830.39	\$86,830.39	\$86,830.39	\$86,830.39

Order Code	Add Options	All Zones
100AL0 ¹	MP7 - 365HP	\$735.00 ¹
100AR0 ¹	MP8 - 445HP	\$2,644.00 ¹
136AB8 ¹	Mack T313 - 13 speed	\$1,629.00 ¹
	Allison 3000 5spd	NA
136AR6 ¹	Allison 4500 5spd	\$20,535.25 ¹
288AA7 ¹	116 gallon single tank	\$363.00 ¹
290AB0 ¹	Dual 50 gallon tanks	\$495.00 ¹
195AA7 ¹	Meritor - RPL25HD	\$157.00 ¹
240AA7 ¹	Mack FXL 14,600 LB	\$759.50 ¹
	14,600 LB Leaf Spring	NC
	Meritor - 40,000 LB	NA
	Mack - 40,000 LB Multileaf	NA
	198" WB	NC
	210" WB	NC
274AA7 ¹	Steel - 300MM x 90MM x 9.5MM	\$376.00 ¹
	Mack Air Disc Brakes	NA
	Mack Air Disc Brakes	NA