



## NORTH CAROLINA SHERIFFS' ASSOCIATION

<b>Name of Dealership</b>	<b>Type of Vehicle</b>	<b>Zone</b>	<b>Base Unit Price</b>
<a href="#"><u>PETERBILT - MODEL 320 AUTOMATED SIDE LOADER (Specification #40)</u></a>			
Peterbilt of Charlotte	2017 Peterbilt Model 320 Automated Side Loader	★Appalachia	\$109,800.00
Peterbilt of Charlotte	2017 Peterbilt Model 320 Automated Side Loader	★Dogwood	\$109,800.00
Peterbilt of Charlotte	2017 Peterbilt Model 320 Automated Side Loader	★Cardinal	\$109,800.00
Peterbilt of Charlotte	2017 Peterbilt Model 320 Automated Side Loader	★Longleaf Pine	\$109,800.00



# **NORTH CAROLINA SHERIFFS' ASSOCIATION**

## **PETERBILT - MODEL 320 AUTOMATED SIDE LOADER**

### **SPECIFICATION #40**

2017 Peterbilt Model 320 Automated Side Loader

**ALL ITEMS FACTORY INSTALLED UNLESS OTHERWISE INDICATED**

**INSTRUCTIONS:** Listed above, you will find the model numbers of the vehicles that will be included in this year's contract.

#### 1. UNIT INFORMATION

- a. Model - 320
- b. Type - Full Truck

#### 2. APPLICATION INFORMATION

- a. Intended Service - Refuse/Landfill
- b. Commodity - Refuse, Scrap

#### 3. BODY

- a. Type - Automated Side Loader
- b. Length (ft) - 24
- c. Height (ft) - 13.5
- d. Max Laden Weight (lb) - 1,000

#### 4. RESTRICTIONS

- a. Length (ft) - 40
- b. Width (in) - 102
- c. Height (ft) - 13.5

#### 5. CHASSIS

- a. Front Axle Load (lbs) - 20,000
- b. Rear Axle Load (lbs) - 46,000
- c. GCW (lbs) - 66,000
- d. Road Conditions: Class A (Highway) - 100 Class B (Highway/Mountain) - 0 Class C (Off Highway) - 0 Class D (Off Road) - 0
- e. Maximum Grade - 6
- f. Wheelbase (in) - 221
- g. Overhang (in) - 76
- h. Front Axle to BOC (in) - 0.1
- i. Cab to Axle (in) - 220.9
- j. Cab to EOF (in) - 296.9
- k. Overall Comb. Length (in) - 355

#### 6. FRONT AXLE AND EQUIPMENT

- a. Dana Spicer D2000F 20,000lb, 3.5" Drop (Factory front axle alignment to improve handling and reduce tire wear. Zerk fittings on tie rod ends, king pins, and draglink ball joints for ease of maintenance and help extend service life of components. Cognis EMGARD (R) FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear and extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions and withstand the stress from high temps , extending component life.

- b. Power Steering Sheppard SD110 Dual (for use with 22,000 lb axle ratings. Glidekote splines on steering shaft extend service life of components)
- c. 5 in Drop IPO 3.5 in, Front Axle

#### 7. REAR AXLE AND EQUIPMENT

- a. Synthetic Axle Lubricant All Axles (Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricants provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.
- b. Anti-Lock Braking System (ABS) 4S4M (ABS-6. Includes air braking system)
- c. SBM Valve (Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.
- d. Dana Spicer D46-170 46,000Lb (Interaxle diff lock air rocker occupied space of one gauge. Laser factory axle alignment to improve handling and reduce tire wear. Magnetic rear axle oil drain plug captures and holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD (R) FE 75W-90 synthetic axle lube provides 1% fuel economy improvement. Reduces wear and extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions and withstand the stress from high temps, extending component life.
- e. Long Stroke Parking Brakes, Drive Axle(s)

#### 8. ENGINE AND EQUIPMENT

- a. Stainless Steel Grille
- b. Exhaust Vertical LH (DPF/SCR transverse mounted)
- c. PACCAR 160 Amp Alternator, Brushed
- d. PACCAR 12V Starter
- e. 3 PACCAR Premium 12V Dual Purpose Batt 2100 CCA (threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.
- f. 18.7 CFM Air Compressor (Furnished on engine. Teflon lined stainless steel braided compressor discharge line)
- g. 2-Speed Fan Clutch For Frequent Start/Stops
- h. PACCAR Fuel Filter/Water Separator, Unheated With water in fuel (WIF) sensor. In addition to the fuel filter supplied with the engine.
- i. High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in.
- j. Heavy Duty Air Cleaner - Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.

#### 9. AIR AND TRAILER EQUIPMENT

- a. Nylon Chassis Hose
- b. Steel Painted Air Tanks (all air tanks are steel with painted finish except when code 4543330 polish aluminum air tanks is also selected ((then exposed air tanks outside the frame rails will be polished aluminum)). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed)
- c. Bendix AD-IS EP Air Dryer with Heater (extended purge ((for use with higher consumption applications)) an integrated system air dryer that incorporates the functions of the air dryer, purge reservoir ((which increases the drying capacity))wet air tank, pressure relief valve, single check valves, and pressure protection valve for air susp and other air accessories. included easy-to-service spin-on dessicant cartridge)

#### 10. FUEL TANKS

- a. DEF Tank 320
- b. Fuel Cooler (required with single fuel tank)

#### 11. CAB AND EQUIPMENT

- a. Peterbilt Driver Seat

- b. Peterbilt Passenger Seat
- c. Two Piece Flat Windshield
- d. Gray Interior Color (includes ABS gray headliner, and rear cab panel, gray vinyl engine tunnel cover)
- e. 4.5 Inch Rubber Flares on Caband Wheel Well Fenders
- f. Vinyl Driver
- g. (1) Air Horn 15" Painted Mounted Under Cab
- h. Peterbilt Electric Windshield Wipers (with intermittent feature)
- i. Adjustable Steering Column - Tilt/Telescope
- j. Steering Wheel with Peterbilt Logo (steering wheel with embossed Peterbilt logo over horn button)
- k. Headlights Dual Rectangular Halogen
  - l. Air Restriction Indicator (mounted on air cleaner or intake piping)
- m. Main Transmission Oil Temperature Gauge (located in driver information display)
- n. Rear Window Back of Cab Std. Tint (18.5" x 54")
- o. (5) LED Clearance with (2) LED Marker Lights (includes five lights mounted on roof of cab and one cab side marker light mounted in front of each cab door)
- p. None Furnished Stop/Tail/Backup Lights (available with full truck only, not available with tractor)
- q. Non-Air Ride Driver
  - r. Low Back Driver
  - s. Non-Air Ride Passenger
  - t. Low Back Passenger
- u. Vinyl Passenger
- v. Backup Alarm Wiring with EOF

## 12. FRAME AND EQUIPMENT

- a. EOF Square without Xmbr (for use with body builder installed crossmember)

## 13. TRANSMISSION AND EQUIPMENT

- a. Console Mounted Push Button Shifter (Allison Transmission)



**NORTH CAROLINA SHERIFFS' ASSOCIATION**  
**PETERBILT - MODEL 320 AUTOMATED SIDE LOADER**  
**SPECIFICATION #40**

**2017 Peterbilt Model 320 Automated Side Loader**

The Peterbilt Model 320 Automated Side Loader purchased through this contract comes with all the standard equipment as specified by the manufacturer for this model and NCSA's base vehicle specification(s) requirements which are included and made a part of this contract's vehicle base price as awarded by specification by zone.

ZONE:	★Appalachia	★Dogwood	★Cardinal	★Longleaf Pine
BASE PRICE:	\$109,800.00	\$109,800.00	\$109,800.00	\$109,800.00

While the North Carolina Sheriffs' Association has attempted to identify and include those equipment items most often requested by participating agencies for full size vehicles, we realize equipment needs and preferences are going to vary from agency to agency. In an effort to incorporate flexibility into our program, we have created specific add/delete options which allow the purchaser to tailor the vehicle to their particular wants or needs.

The following equipment delete and add options and their related cost are provided here to assist you in approximating the total cost of the type vehicle(s) you wish to order through this program. Simply deduct the cost of any of the following equipment items you wish deleted from the base unit cost and/or add the cost of any equipment items you wish added to the base unit cost to determine the approximate cost of the type vehicle(s) you wish to order.

NOTE: An official listing of all add/delete options and their prices should be obtained from the appropriate dealer in your zone when preparing your order. Additional add/delete options other than those listed here may be available through the dealers, however, those listed here must be honored by the dealers in your zone at the stated prices.

<b>VEHICLE:</b>	Model 320 Automated Side Loader			
<b>DEALER:</b>	Peterbilt of Charlotte	Peterbilt of Charlotte	Peterbilt of Charlotte	Peterbilt of Charlotte
<b>ZONE:</b>	★Appalachia	★Dogwood	★Cardinal	★Longleaf Pine
<b>BASE PRICE:</b>	\$109,800.00	\$109,800.00	\$109,800.00	\$109,800.00

Order Code	Delete Options	All Zones
0651090 <sup>1</sup>	Omit rear mudflaps and hangers <i>Standard<sup>1</sup></i>	Std <sup>1</sup>
	PHP 10 Iron PreSet PLUS Hubs <i>Unable to quote truck without brakes<sup>1</sup></i>	Std <sup>1</sup>
	18.7 CFM Air Compressor (Furnished on engine. Teflon lined stainless steel braided compressor discharge line) <i>Unable to quote without air compressor<sup>1</sup></i>	Std <sup>1</sup>
	1710 Driveline Interaxle, Tandem Rear Axles <i>Cannot delete interaxle.<sup>1</sup></i>	Std <sup>1</sup>
	Aluminum Space Saver Battery Box LH Back Of Cab <i>Must include batteries. Cannot delete<sup>1</sup></i>	Std <sup>1</sup>
	Standard Paint Color Selection	Std
	Cummins ISX Power	NA
	Bendix Air Came Rear Drum Brakes 16.5 x 8.6 (Inc automatic slack adjusters and outboard mounted brake drums. Refer to TSB 11-57 for more information) <i>Cannot delete brakes<sup>1</sup></i>	NA <sup>1</sup>
	FF: BR 20 Ply 315/80R22.5 M860A (diameter = 42.8 inches; SLR = 19.9 inches) <i>Cannot quote without tires and wheels<sup>1</sup></i>	Std <sup>1</sup>
	RR: Accur Steel Armor 50344PK 22.5X8.25Heavy Duty, 5 Hand Holes	Std

Order Code	Add Options	All Zones
	10-3/4in Steel Rails 343-450in10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	Std
0601500 <sup>1</sup>	Full steel inner liner	\$383.00 <sup>1</sup>
0620110 <sup>1</sup>	FEPTO Provision 9 in Bumper Extension (includes 1350 series front drive PTO attachment provision, radiator with PTO cut-out in grille, radiator protection sleeve, and bumper extension)	\$446.00 <sup>1</sup>
1380240 <sup>1</sup>	Dana Spicer Wide Track IPO Std., Front Axle (71" KPI IPO 69" E1202, E1322, E1462, D2000F front axles. For improved turning radius.	\$30.00 <sup>1</sup>
1114040 <sup>1</sup>	Taper Leaf Springs, Shocks 23,000lbs (standard with heavy resistance shocks)	\$231.00 <sup>1</sup>
1390540 <sup>1</sup>	Dust Shields, CAM Brakes, Front Axle	\$16.00 <sup>1</sup>
1391390 <sup>1</sup>	Long Stroke Brakes, Front Axle	\$16.00 <sup>1</sup>
1392970 <sup>1</sup>	Heavy Duty CAM Bushings, Steer Axle	\$17.00 <sup>1</sup>
1380280 <sup>1</sup>	Bendix Air Cam Front Drum Brakes 16.5x7For use with 16,000 lbs to 22,000 lbs steer axles or front drive axles. Includes automatic slack adjusters & outboard mounted brake drums.	\$67.00 <sup>1</sup>
1680440 <sup>1</sup>	Refuse Service Brakes, Steer and Drive Axle(s)	NC <sup>1</sup>
1680450 <sup>1</sup>	Rear Brake Camshaft Reinforcement	\$33.00 <sup>1</sup>
1680460 <sup>1</sup>	Heavy Wall, Drive Axle (s)	\$318.00 <sup>1</sup>
1616290 <sup>1</sup>	PHP10 Aluminum PreSet PLUS Hubs	\$1,124.00 <sup>1</sup>
	Ratio 5.38 Rear Axle	Incl.

<b>VEHICLE:</b>	Model 320 Automated Side Loader			
<b>DEALER:</b>	Peterbilt of Charlotte	Peterbilt of Charlotte	Peterbilt of Charlotte	Peterbilt of Charlotte
<b>ZONE:</b>	★ Appalachia	★ Dogwood	★ Cardinal	★ Longleaf Pine
<b>BASE PRICE:</b>	\$109,800.00	\$109,800.00	\$109,800.00	\$109,800.00

	Hendrickson Haulmaax HMX 460 46,000lb, 54 in Axle (spacing, 60k creep rating)	Incl.
2057548 <sup>1</sup>	ISX12 350R 350@1800 GOV@2100 1450@1100Refuse Service (2013 Emissions) Includes aluminum flywheel housing. Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life.N21320 N205 120..Standard Maximum Speed Limit [LSL]N21330 N207 0....Expiration DistanceN21340 P112 120..Hard Maximum Speed LimitN21350 P001 64...Maximum Accelerator Pedal Vehicle SpeedN21360 P110 0....Accelerator Lower DroopN21370 P059 64...Maximum Cruise SpeedN21380 P111 0....Cruise Control Lower DroopN21400 N203 252..Reserve Speed Function Reset DistanceN21410 N202 0....Maximum Cycle DistanceN21420 N206 10...Maximum Active DistanceN21430 N201 0....Reserve Speed Limit OffsetN21440 P015 No...Engine Protection ShutdownN21450 P026 Yes..Gear Down ProtectionN21460 P046 1400.Max PTO SpeedN21470 P062 No...Cruise Control Auto ResumeN21480 P068 No...Auto Engine Brake in CruiseN21500 N209 0....Expiration DistanceN21510 P520 Yes..Enable Idle Shutdown Park Brake SetN21520 P030 5....Timer SettingN21530 P233 Yes..Enable Impending Shutdown WarningN21540 P234 60...Timer For Impending Shutdown WarningN21550 P516 35...Engine Load ThresholdN21570 P031 No...Idle Shutdown Manual OverruleN21590 P230 Yes..Enable Hot Ambient Automatic OverruleN21610 P172 40...Low Ambient Temperature ThresholdN21620 P173 60...Intermediate Ambient Temperature ThresholdN21630 P171 80...High Ambient Temperature Threshold	\$8,685.00 <sup>1</sup>
	Engine Idle Shutdown Timer Enabled	
	Enable EIST Ambient Temp Overrule	\$0.00
	Eff EIST NA Expiration Miles	\$0.00
2539220 <sup>1</sup>	Battery Jumper Terminals Mtd in Front (of battery box)	\$104.00 <sup>1</sup>
	CARB Engine Idling Compliance (PACCAR PX-7, PX-9 and MX, Cummins ISL, ISM and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	\$0.00
	Engine Protection Shutdown (includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature)	\$0.00
	Effective VSL Setting NA	\$0.00
	Remote PTO And Throttle Provision	\$0.00
2539740 <sup>1</sup>	Kissling Battery Disconnect SwitchMounted on battery box	\$128.00 <sup>1</sup>
3381770 <sup>1</sup>	Curved Tip Standpipe (s)	\$27.00 <sup>1</sup>
3387890 <sup>1</sup>	36in Ht, 5in Dia Chrome, Clear Coat Standpipe(s)	\$35.00 <sup>1</sup>
	Stranded copper battery cables are double aught (00) or larger to reduce resistance	Incl.
	Kissling Battery Disconnect Switch (mounted on battery box) <i>Included in previous section</i> <sup>1</sup>	NA <sup>1</sup>
	2-Speed Fan Clutch for Frequent Start/Stops	Incl.
4052420 <sup>1</sup>	Allison 4500 RDS-P Transmission, Gen 5 (Rugged duty series. Includes rear transmission support, transynd transmission fluid, and water oil heat exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the mode and up and down buttons. A wrench icon will also be included to indicate when the transmission fluid,filter or clutches need servicing. ((Suited for vehicles operating on/off highway and/or requiring PTO operation) forward ratios: 1st - 4.70, 2nd - 2.21, 3rd - 1.53, 4th -	\$8,864.00 <sup>1</sup>

<b>VEHICLE:</b>	Model 320 Automated Side Loader			
<b>DEALER:</b>	Peterbilt of Charlotte	Peterbilt of Charlotte	Peterbilt of Charlotte	Peterbilt of Charlotte
<b>ZONE:</b>	★ Appalachia	★ Dogwood	★ Cardinal	★ Longleaf Pine
<b>BASE PRICE:</b>	\$109,800.00	\$109,800.00	\$109,800.00	\$109,800.00

	1.00, 5th - 0.76, 6th - 0.67 / reverse ratios: DR - (5.55))	
4210150 <sup>1</sup>	1810 Driveline, 1 Midship BearingSlotted Rubber Mount	\$110.00 <sup>1</sup>
4256870 <sup>1</sup>	Allison Output Function S Neutral Indicator (For PTO, required on refuse packer applications. With this configuration neutral only, PTO engagement is permitted only when the transmission is in Neutral. Once the transmission is in neutral, the PTO is automatically engaged and fast idle is initiated when the PTO switch is switched on. Also, with this configuration pack-on-the-fly, the PTO is automatically engaged and fast idle is initiated when the PTO switch is on concurrently with shifting of the transmission to neutral.	NC <sup>1</sup>
4250720 <sup>1</sup>	Allison FuelSense Not Desired	NC <sup>1</sup>
4256740 <sup>1</sup>	Allison 6-Speed Configuration, Wide Ratio Gears (Allison 4500 transmission only)	NC <sup>1</sup>
4520420 <sup>1</sup>	Berg Pull Cord Drain Valve (s) - All air tanks	NC <sup>1</sup>
	FF: Accur Stl Armor 29039PK 22.5 x 9.00 (PHP 10-5 hand holes)	Incl.
	RR: BR 14ply 11R22.5 M710 EcopiaDiameter = 41.8 inches; SLR = 19.5 inches	Incl.
	Code - rear tire qty 8	Incl.
	Code- Rear rim qty 8	Incl.
	26in Aluminum 80 Gallon Fuel Tank LH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks. conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability and reduce potential for leaks) <i>Not compatible with configuration. Tank on Right side</i> <sup>1</sup>	NA <sup>1</sup>
	Location LH BOC Rear Most 80 Gallon	NA
	DEF Tank Mounted LH BOC (models 210, 220, and 320 mounted LH cab fender)	Std
	Standard DEF to Fuel Ratio 2:1 or Greater	Std
5652850 <sup>1</sup>	Perforated Metal Anti-Siphon Device(s)(Requires Engineering review with Arctic Fox or Split Fuel Tanks)	\$32.00 <sup>1</sup>
6122810 <sup>1</sup>	Steel Bumper Swept Back Painted (requires bumper extension, includes two front tow eyes with pins)	\$36.00 <sup>1</sup>
6132400 <sup>1</sup>	Notched Top Flange Of Bumper Includes cutout in radiator for F/O fepto	\$238.00 <sup>1</sup>
6030360 <sup>1</sup>	Mount Space Saver Battery Box Top Of Box 8inBelow top of frame	\$50.00 <sup>1</sup>
6939400 <sup>1</sup>	Air Ride Driver	\$128.00 <sup>1</sup>
7322010 <sup>1</sup>	Combo Fresh Air Heater/Air Conditioner (with radiator mounted condenser, dedicated side window defrosters, bi-level heater/defroster controls, 54,500 BTU/HR and silicone heater hoses <i>Quote includes ceiling mtd AC</i> <sup>1</sup>	NA <sup>1</sup>
7561260 <sup>1</sup>	Black LH/RH Tri-plane Mirrors, Heated, Mounted to Driver-Door & Passenger Front of Cab. Features: Heated on All Three Surfaces, Upper/Lower Mirrosr are Convex and Middle is a Flat Pane Motorized Mirror. Right Click on Option and Select Picture to See a Picture of the Mirror.	\$72.00 <sup>1</sup>
7725740 <sup>1</sup>	Mid-level Speaker Package for cab (4 speakers)	\$70.00 <sup>1</sup>
8133960 <sup>1</sup>	Daytime Running Lights (required on all Canadian units)	\$41.00 <sup>1</sup>
7725725 <sup>1</sup>	ConcertClass without CD, Includes BT Phone (includes audio, am/fm, wb, usb, and mp3)	\$267.00 <sup>1</sup>
7851330 <sup>1</sup>	Cab Tilt Pump Air Assist	\$92.00 <sup>1</sup>



<b>VEHICLE:</b>	Model 320 Automated Side Loader			
<b>DEALER:</b>	Peterbilt of Charlotte	Peterbilt of Charlotte	Peterbilt of Charlotte	Peterbilt of Charlotte
<b>ZONE:</b>	★ Appalachia	★ Dogwood	★ Cardinal	★ Longleaf Pine
<b>BASE PRICE:</b>	\$109,800.00	\$109,800.00	\$109,800.00	\$109,800.00

6501090 <sup>1</sup>	53in LCF ProBilt Cab RH Drive Use with auto trans. Includes steel frames with alum and fiberglass panels, all alum doors, dual door stops, door locks, tinted safety glass thru-out, cab and door mounted entry grab handles, 65 degree hydraulic tilt, stainless steel grille, dual rear cab fenders, service module BOC (cab tilt pump, oil fill and dipstick, coolant fill and check, fluid fill and dipstick for auto trans), door mounted armrests, power windows, full insulation, rubber floor mats, ergonomic center control console, removable instrument panel, Driver Information Display, LED backlit gauges, pull down windshield sunshade, 16in steering wheel with integrated horn button, tilt/telescopic adjustable column, over-door storage, driver and passenger side cup holders, USB charging port and 12VDC charging outlet, header includes HVAC controls, rear cab corner windows, 18in bolt-on step on each side, self-canceling turn signals and Front Directional and Side Mounted Turn Signals.	\$715.00 <sup>1</sup>
7900090 <sup>1</sup>	Triangle Reflector Kit Shipped Loose	NC <sup>1</sup>
7040020 <sup>1</sup>	Diamond Plate Floor Covering on Driver side floor in place of Rubber Mat. In Dual Steer application RH Diamond Plate covering is standard. Single drive applications the Diamond Plate is optional.	NC <sup>1</sup>
8021015 <sup>1</sup>	Air Application Gauge Located in Driver Information Display	NC <sup>1</sup>
8021120 <sup>1</sup>	Warning Light Battery Disconnect, Switch Engaged (Marker light) external mounted.	NC <sup>1</sup>
	Heavy Duty Emissions Surcharge	Incl.
	Presentation Created Using Featured Spec (for model)	Incl.
	Base Coat/Clear Coat	Incl.
	N85020 A - L0006EB WHITE - STAND	Incl.
	N85500 CAB ROOF L0006EB WHITE-STAND	Incl.
	N85200 FRAME N 0001EA BLACK	Incl.
	N85700 BUMPER N0001EA BLACK	Incl.
	Shipping Destination00(Specify by narrative attached to option code). In Presentation Information screen add "See Instructions" for the Shipping Destination instead of Dealer code.N89900 New Way TrucksN89910 101 State StN89920 Scranton, IA 51462N89930 712) 652-3396 <i>Will be changed to reflect the exact delivery location</i> <sup>1</sup>	Incl. <sup>1</sup>