

NORTH CAROLINA SHERIFFS' ASSOCIATION

Name of Dealership Type of Vehicle		Zone	Base Unit Price
PETERBILT - MODEL 348 REAR LOAI	DER/PUSH-OUT X (Specification #48)		
Peterbilt of Knoxville	2017 Peterbilt Rear Loader/Push Out Model 348	★ Appalachia	\$84,155.00
Peterbilt of Knoxville	2017 Peterbilt Rear Loader/Push Out Model 348	★Dogwood	\$84,155.00
Peterbilt of Knoxville	2017 Peterbilt Rear Loader/Push Out Model 348	★Cardinal	\$84,155.00
Peterbilt of Knoxville	2017 Peterbilt Rear Loader/Push Out Model 348	★ Longleaf Pine	\$84,155.00



NORTH CAROLINA SHERIFFS' ASSOCIATION

PETERBILT - MODEL 348 REAR LOADER/PUSH-OUT X SPECIFICATION #48

2017 Peterbilt Rear Loader/Push Out Model 348

ALL ITEMS FACTORY INSTALLED UNLESS OTHERWISE INDICATED

INSTRUCTIONS: Listed above, you will find the model numbers of the vehicles that will be included in this year's contract.

1. <u>BODY</u>

- a. Tandem Rear Loader Small Roll-off
- b. Max Laden Weight 1000 lbs
- c. Height 8.5 ft
- d. Length 24 ft

2. TRAILER

- a. Corner Radius 0 in
- b. Kingpin Inset 0 in
- c. Height 0 ft
- d. Length 0 ft

3. RESTRICTIONS

- a. Height 13.5 ft
- b. Width 102 in
- c. Length 65 ft

4. CHASSIS

- a. Fr Axie Load 18180 lbs
- b. Rr Axie Load 46000
- c. G.C.W. 62000
- d. Road Conditions: Class A (Highway)-100, Class B (Hwy/Mtn)-0, Class C (Off-Hwy)-0, Class D (Off-Road)-0
- e. Maximum Grade: -6
- f. Wheelbase 220 in
- g. Overhang -93.79999 in
- h. Fr Axle to BOC -69.8 in
- i. Cab to Axle 150.2 in i. Cab to EOF 244.0
- k. Overall Comb. 352 in

5. FRAME & EQUIPMENT

- a. Three-Piece Crossmembers 0
- b. EOF Square without Xmbr For use with body builder installed crossmember. 0
- c. Omit Rear Mudflaps and Hangers 0

6. REAR AXLE & EQUIPMENT

a. Synthetic Axle Lubricant All Axles - Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow

to protect gears in extreme cold conditions and withstand the stress from high temperatures extending component life.

- b. SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system. 0
- c. Stability System Not Selected or Not Available 0
- d. Bendix Air Cam Rear Drum Brakes 16.5x7 Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums
 0
- e. Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system. 0

7. ENGINE & EQUIPMENT

- a. Exhaust Single RH Side of Cab DPF/SCR RH under cab. Includes cab entry RH under cab and full round stainless steel exhaust guard. 0
- b. Radial Seal, Dry Tape Air Cleaner, Frontal Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake. 0
- c. High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEBPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in, -0
- d. Spin-on Fuel Filter/Water Separator, Unheated Frame Mounted. In addition to the fuel filter supplied with the engine.
- e. 18.7 CFM Air Compressor Furnished on engine. Teflon lined stainless steel braided compressor discharge line. 0 f. PACCAR 12V Starter 0

8. TRANSMISSION & EQUIPMENT

- a. Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outsid ethe frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narrative requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed. 0
- b. Nylon Chassis Hose 0

9. AIR & TRAILER EQUIPMENT

- a. Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed. 0
- b. Nylon Chassis Hoses 0

10. TIRE & WHEELS

a. RR: Accur Stl Armor 50291PK 22.5x8.25 - Heavy Duty, Two Hand Holes - 0

11. FUEL TANKS

a. DEF Tank Small - 0

12. BATTERY BOX & BUMPER

a. Aftertreatement RH U/C Alum Non-Slip Cab Entry - Step. DPF/SCR for diesel engines, catalyst for natural gas engines. On models 579 specifying chassis fairings, the box will be aerodynamic. - 0

13. CAB & EQUIPMENT

- a. Alum Cab 108in BBC Metton Hood w/Bright Crown Includes view window RH door and convex mirror over RH door. - 0
- b. Peterbilt UltraRide Driver Seat 0
- c. Air Ride Driver 0
- d. High Back Driver 0
- e. Vinvl Driver 0
- f. Vinyl Passenger 0

- g. Adjustable Steering Column Tilt Only 0
- h. Steering Wheel with Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button 0
- i. Vinyl Passenger 0
- j. Main Instrumentation Panel, Graphics Display -Includes speedometer with tripodometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature. low oil pressure and low air pressure warning lights w/audible alarms, high beam, turn signal, low fuel, parking brake, and ice indicators; mult-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges 0
- k, Headlights Composite Fender Mounted Integral Park, Turn, and Side Marker 0
- 1. (5) Marker Lights, Aero LED Light Emitting Diodes 0
- m. Interior Grey/Black Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal:, (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash- 0
- n. Day Cab Rear Window
- o. One Piece Curved Windshield 0
- p. Combo Fresh Air Heater/Air Conditioner -With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses. 0
- q. Peterbilt Electric Windshield Wipers with Intermittent Feature. 0
- r. (5) Marker Lights, Aero LED Lighting Emitting Diodes 0
- s. Air Restriction Indicator Mounted on air cleaner or intake piping. 0

14. FRONT AXLE & EQUIPMENT

a. PHP10 Aluminum LMS Hubs - 11-1/4in bolt circle. Includes a supplier extended coverage up to 3 years/ 350,000 miles for bearing & seals. - 0



NORTH CAROLINA SHERIFFS' ASSOCIATION

PETERBILT - MODEL 348 REAR LOADER/PUSH-OUT X SPECIFICATION #48

2017 Peterbilt Rear Loader/Push Out Model 348

The Peterbilt Rear Loader/Push Out Model 348 purchased through this contract comes with all the standard equipment as specified by the manufacturer for this model and NCSA's base vehicle specification(s) requirements which are included and made a part of this contract's vehicle base price as awarded by specification by zone.

While the North Carolina Sheriffs' Association has attempted to identify and include those equipment items most often requested by participating agencies for full size vehicles, we realize equipment needs and preferences are going to vary from agency to agency. In an effort to incorporate flexibility into our program, we have created specific add/delete options which allow the purchaser to tailor the vehicle to their particular wants or needs.

The following equipment delete and add options and their related cost are provided here to assist you in approximating the total cost of the type vehicle(s) you wish to order through this program. Simply deduct the cost of any of the following equipment items you wish deleted from the base unit cost and/or add the cost of any equipment items you wish added to the base unit cost to determine the approximate cost of the type vehicle(s) you wish to order.

NOTE: An official listing of all add/delete options and their prices should be obtained from the appropriate dealer in your zone when preparing your order. Additional add/delete options other than those listed here may be available through the dealers, however, those listed here must be honored by the dealers in your zone at the stated prices.

 DEALER:
 Peterbilt of Knoxville
 Peterbilt of Knoxville
 Peterbilt of Knoxville
 Peterbilt of Knoxville
 Peterbilt of Knoxville

 ZONE:
 ★ Appalachia
 ★ Dogwood
 ★ Cardinal
 ★ Longleaf Pine

Order Code	Delete Options	All Zones
	Engine Idle Shutdown Timer Enabled – 0	Std
	Enable EIST Ambient Temp Overrule – 0	Std
	Eff EIST NA Expiration Miles – 0	Std
	Effective VSL Setting NA – 0	Std
	CARB Engine Idling Compliance - PACCAR PX-7, PX-9 and MX, Cummins ISL, ISM and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard. -0	Std
2521090 ¹	Immersion Type Block Heater 110-120V - Standard location is center left hand under cab and includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running. -2	\$81.00 ¹
2140320 1	Remote Throttle Control Provision - Control Switch & Wiring EOF Only - 4	\$77.00 ¹
2539740 ¹	Kissling Battery Disconnect Switch - Mounted on battery box – 1	\$189.00 ¹
30105400 1	Engine Protection Shutdown - Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature. -0	\$4.001
2074505 1	PACCAR PX-9 350@2000 GOV@200 1000@1400 - (2013 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life.N21320 N205 120Standard Maximum Speed Limit [LSL]N21330 N207 0Expiration DistanceN21340 P005 120Hard Maximum Speed LimitN21350 P001 0Accelerator Lower DroopN21370 P059 70Maximum Cruise SpeedN21380 P111 0Cruise Control Lower DroopN21400 N203 252 Reserve Speed Function Reset DistanceN21410 N202 0Maximum Cycle DistanceN21420 N206 10Maximum Active DistanceN21430 N201 0Reserve Speed Limit OffsetN21440 P015 NoEngine Protection ShutdownN21450 P026 NoGear Down ProtectionN21460 P046 14000.Max PTO SpeedN21470 P062 NoCruise Control Auto ResumeN21480 P068 NoAuto Engine Brake in CruiseN21500 N209 0Expiration DistanceN21510 P520 YesEnable Idle Shutdown Park Brake SetN21520 P030 5Timer SettingN21530 P233 YesEnable Impending Shutdown WarningN21540 P234 60Timer For Impending Shutdown WarningN21550 P516 35Engine Load ThresholdN21570 P030 NoIdle Shutdown Manual OverruleN21590 P230 YesEnable Hot Ambient Automatic OverruleN21610 P172 40Low Ambient Temperature ThresholdN21620 P173 60Intermediate Ambient Temperature ThresholdN21630 P171 80High Ambient Temperature Threshold	
2621000 1	2-Speed Fan Clutch for Frequent Start/Stops - 0	\$343.001
3381770 ¹	Curved Tip Standpipes(s) - 0	\$43.00 ¹
3010400 1	Engine Protection Shutdown - Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature 0	\$4.001
253810 ¹	2 PACCAR AGM 12V A Batteries 1600 CCA - Stranded copper battery cables are double aught (00) or larger to reduce resistance 0	\$172.00 ¹
3387890 1	36in Ht, 5in Dia Chrome, Clear coate Standpipe(s) - 4	\$52.00 ¹
	FF: Alcoa 893657 LVL1 22.5x9.00 Alm Whl38	NA

 DEALER:
 Peterbilt of Knoxville
 Peterbilt of Knoxville
 Peterbilt of Knoxville
 Peterbilt of Knoxville
 Peterbilt of Knoxville

 ZONE:
 ★ Appalachia
 ★ Dogwood
 ★ Cardinal
 ★ Longleaf Pine

Aluminum Space Saver Battery Box RH Back of Cab84	NA
Aluminum Channel Bumper Stainless Steel Clad - Two Tow Pins4	NA
PACCAR 130 Amp Alternator, Brushless w/Voltage - Regulator. Remote Sense is not available or needed with the PACCAR Alternator. At low engine RPM, the PACCAR Alternator puts out 80 amps verses 60 amps on other alternators. 12 volt system with circut protection for reliable easy maintenance & service. Weather pack silicone sealed electrical chassis connectors enhance value, durability, reliability. Wires numbered every 4" or less18	NA

Order Code	Add Options	All Zones
4052110 ¹	Allison 3000 RDS-P Transmission, Gen 5Rugged Duty Series. Includes Rear Transmission Support, TranSynd Transmission Fluid, and Water Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter clutches on the shift selector. This information may be displayed using the Mode and UP and Down buttons. A wrench icon with also be included to indicate when the transmission fluid, filter or clutches need servicing. (Suited for vehicles operating on/off highway and/or requiring PTO operation) Forward Ratios: 1st-4.59, 2nd 1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65/Reverse Ratios: DR-(5.03) - 110	\$9,936.001
	1710 HD Driveline, 2 Midship Bearing - 100	Incl.
	Allison FuelSense Not Desired - 0	NC
4266920 1	Dash Mounted Push Button Shifter - 0	\$619.00 ¹
	Allison 6-Speed Configuration, Wide Ratio Gears - 0	NC
	Allsion Output Function S Neutral Indicator - For PTO. Required on Refuse Packer Applications. With this configuration NEUTRAL only, PTO engagement is permitted only when the transmission is in Neutral. Once the transmission is the Neutral, the PTO switched On. Also, with this configuration Pack-on-the-fly, the PTO is automatically engaged and fast idle is initiated when the PTO switch is On concurrently with shifting of the transmission to Neutral 0	NC
	Allison PTO enable on Mode Button - The PTO function C can be either on remote wire, or mode button. It depends on the selected input/output package. This function is enabled with the MODE button. Enabling the function alerts the TCM that PTO operation has been requested by the operator. When the function is enabled and all of the required operating conditions exist, the TCM activates Output G: PTO Enable by switching power to wire 130. When this function is enabled, the TCM disables the variabl	Incl.
	Auto Neutral Activates with Parking Brake - 0	\$16.00
	Bendix AD-IS EP Air Dryer with Heater - Extended Purge (for use with higher air consumption applications). An integrated system air dryer that incorporates the functions of the air dryer, purge reservoir (which increases the drying capacity), wet air tank, pressure relief valve, single check valves, and pressure protection vavle for air susp and other air accessories. Includes easy-to-service spin-on dessicant cartridge 39	NC
165193 1	Body Connections 5ft BOC - Junction Box contains light and power circuits for Body Connections located 5ft from BOC 4	\$132.00 ¹
	Berg Pull Cord Drain Valve(s) - All Air Tanks - 0	\$5.00

DEALER: Peterbilt of Knoxville Peterbilt of Knoxville Peterbilt of Knoxville Peterbilt of Knoxville

ZONE: ★Appalachia ★Dogwood ★Cardinal ★Longleaf Pine

Bendix AD-IS EP Air Dryer with Heater - Extended Purge (for use with high air consumption applications). An integrated system air dryer that incorprates the functions of the air dryer, purge reservoir (which increases the drying capacity), wet air tank, pressure relief valve, single check valves, and pressure protection valve for air susp and other air accessories. Includes easy-to-service spin-pm dessicant cartridge 39	\$139.00
Body Connections 5ft BOC - Junction Box contains light and power circuts for Body Connections located 5ft from BOC 4	\$132.00
FF: MN 20ply 315/80R22.5 XZA1 - Diameter = 42.5 inches; SLR = 19.6 inches. Compares to Goodyear G291 and Bridgestone R294 tread50	\$801.00
RR: MN 16ply 11R22.5 XDE M/S - Diameter=41.7 inches; SLR = 19.4 inches. Compares to Goodyear G328 and Bridgestone M711 tread 76	\$441.00
Code-rear Tire Qty 08 - 0	Incl.
Code-rear Rim Qty 08 -0	Incl.
RR: Accur STL Armor 50291PK 22.5x8.25 Heavy Duty, Two Hand Holes - 44	Incl.
Location LH U/C 70 Gallon - 0	Std
DEF Tank Mounted LH BOC - Models 210, 220 and 320 mounted LH cab fender - 0	Std
Standard DEF to Fuel Ratio 2:1 or Greater - 0	Std
Sever Service Cab Package #1 - Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab 39	\$94.00
Rubber Fender Lips 2 Inch Wide - 8	\$94.00
(2) Person Passenger Seat - 0	\$351.00
Stainless Steel Mirrors 7X16 with Heat Element - Right Click on Option to see Picture in Product Portfolio - 2	\$70.00
Low Back Passenger - 0	Std
Stainless Steel Mirrors 7x16 with Heat Element - Right Click on Option to see Picture in Product Portfolio - 2	\$198.00
(2) Convex 8 Inch SS Mirror - Centered mounted under mirror bracket. If rear view mirror are heated, the convex mirrors will be heated. Option includes dual door stops4	\$70.00
(1) Air Horn 15in Painted - Mounted under cab 8	\$161.00
LED Stop/Turn/Tail - 40204 Backup, bracket mounted LH/RH EOF - 2	\$19.00
Standard Speaker Package For Cab - (2) Speakers - 4	\$115.00
ConcertClass Without CD, Includes BT Phone and Audio, AM/FM, WB, USB and MP3 10	\$323.00
CB Terminals/Wiring Mtd Under Heater - 0	\$32.00
(2) Addl Dome/Reading Lights, Ceiling Mounted - 0	\$38.00
Standard Paint Color Selection -0	Std
(1) Color Axalta Two Stage - Cab/HoodBase Coat/Clear CoatN85020 A - L0006EB WHITE-StandN85400 HOOD TOP L0006EY WHITE - StandN85500 CAB ROOF L0006EY WHITE - StandN85200 FRAME N0001EA BLACKN85300 FENDER L0006EY WHITE - StandN85700 BUMPER N0001EA BLACK -0	\$1,037.00

 DEALER:
 Peterbilt of Knoxville
 Peterbilt of Knoxville
 Peterbilt of Knoxville
 Peterbilt of Knoxville
 Peterbilt of Knoxville

 ZONE:
 ★ Appalachia
 ★ Dogwood
 ★ Cardinal
 ★ Longleaf Pine

Medium Duty Emmissions Surcharge - 0	Incl.
0	Incl.
Model 348 - 10,660	Std
Refuse, Scrap – 0	NC
Refuse/Landfill - Truck which picks up refuse or recycled material from curbside containers in residential area. Operation typically includes very frequent stops and starts. Unloading can be at transfer station or landfill (may enter landfill)—0	NC
United State Registry - 0	Std
Rear Loader/Push-Out - 0	NC
Other - Secondary manufacturer (specify by narriative) N02000 nono - 0	Incl.
10-5/8in Steel Rails to 326-384 in - 10.65x3.45x.313 Dimension, 1,776,000RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair – 328	Incl.
220in Wheelbase - 0	Incl.
Full Steel Inner Liner - 653	\$770.00
Taper Leaf Springs, Shocks 20,000 lbs - Standard with Heavy Resistance Shocks - 0	Incl.
Dana Spicer D21202l 12,000lb,3.5in Drop - Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins & draglink ball joints for ease of maintenance & help extend service life of components. Cognis EMGARD FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the s	(\$1,200.00)
Power Steering Sheppard HD94 Dual - For use with 16,000 to 20,000 lb axle ratings 0	Incl.
Power Steering Reservoir Frame Mounted w/Cooler - 0	Incl.
Bendix Air Cam Front Drum Brakes 16.5x6 - For use with 14,601lbs to 22,000lbs steer axles or FSD16 front drive axles. Includes automatic slack adjusters & outboard mounted brake drums - 0	(\$725.00)
Dust Shield, CAM Brakes, Front Axle – 0	\$26.00
Gusseted Cam Brackets, Steer Axle - 0	\$24.00
26in Aluminum 60 Gallon Fuel Tank LH U/C - Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduceds chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential leaks117	\$62.00
Dana Spicer D46-170 46,000lb - Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life 2,525	Incl.
Long Stroke Parking Brakes, Drive Axle(s) - 20	Incl.
Dust Shields for Cam Brakes, Drive Axle(s) - 15	\$30.00
Diff Lock Both Axles (Air Rocker Switch occupies the space of one gauge) 60	\$2,102.00

DEALER:Peterbilt of KnoxvillePeterbilt of KnoxvillePeterbilt of KnoxvillePeterbilt of KnoxvilleZONE:★ Appalachia★ Dogwood★ Cardinal★ Longleaf PineBASE PRICE:\$84,155.00\$84,155.00\$84,155.00\$84,155.00

Lube Pump, Drive Axle(s) - 36	\$258.00
Upsize Parking Brake - 0	\$76.00
Heavy Duty Brake Drums, Drive Axle(s) - Use with 16.5x7 Brakes - 21	Incl.
Tandem Drive Axle (Model 348) - 0	Std
Ratio 5.57 Rear Axle - 0	Incl.
Hendrickson Haulmaxx HMX460 46,000lb, 54in Axle - Spacing, 60K Creep Rating - 593	Incl.
Tracking Rods, Rubber Center Bearings - R(T/E) 40523 - 99	NA
12,000	NC
14,000	\$765.00
18,000	\$1,566.00
20,000	\$1,566.00
40,000	\$8,184.00
44,000	\$9,256.00
46,000	\$10,466.00
PX9 px9 300 hp 1	\$1,683.00 ¹
8, 9, 10, 13 Manual 10 speed 1	\$307.00 ¹
3,000, 3,500, 4,500 Allision Transmission 3000 rdsp allision 1	\$9,936.001
180-320	\$222.00
Air Driver	Std
Air Passenger	\$199.00
Stationary Driver and Passenger	(\$141.00)
Two Man Passenger	\$351.00
AC	Std
AM included with blue tooth 1	Incl. ¹
FM included w bluetooth 1	Incl. ¹
Bluetooth	\$373.00
CB cobra 1	\$237.00 ¹
Aluminum	Std
50-110 Gallons 100 gallon ¹	\$89.001
·	