



NORTH CAROLINA SHERIFFS' ASSOCIATION

Name of Dealership	Type of Vehicle	Zone	Base Unit Price
<u>PETERBILT - MODEL 348 ROLL-OFF (Specification #49)</u>			
Peterbilt of Knoxville	2017 Peterbilt Model 348	★Appalachia	\$110,205.00
Peterbilt of Knoxville	2017 Peterbilt Model 348	★Dogwood	\$110,205.00
Peterbilt of Knoxville	2017 Peterbilt Model 348	★Cardinal	\$110,205.00
Peterbilt of Knoxville	2017 Peterbilt Model 348	★Longleaf Pine	\$110,205.00



NORTH CAROLINA SHERIFFS' ASSOCIATION

PETERBILT - MODEL 348 ROLL-OFF **SPECIFICATION #49**

2017 Peterbilt Model 348

ALL ITEMS FACTORY INSTALLED UNLESS OTHERWISE INDICATED

INSTRUCTIONS: Listed above, you will find the model numbers of the vehicles that will be included in this year's contract.

1. BASE MODEL

- a. Model 348 - 10,660
- b. Refuse/On-Highway - Truck tractor which hauls refuse, recycled material, etc. Includes roll-on/roll-off container movement, as well as hauling refuse from transfer stations to, but not into, landfills. - 0
- c. Roll-Off - 0
- d. United States Registry - 0

2. RESTRICTIONS

- a. Length 65 feet
- b. Width 102 inches
- c. Height 13.5 feet

3. CHASSIS

- a. Fr Axle Load - 20000 lbs
- b. Fr Axle Load - 44000 lbs
- c. G.C.W. - 64000 lbs
- d. Road Conditions - Class A (Highway)- 100
- e. Maximum Grade - 6
- f. Wheelbase - 262 inches
- g. Overhang - 75 inches
- h. Fr Axle to BOC - 72.2
- i. Cab to Axle - 189.8 inches
- j. Cab to EOF - 264.8 inches
- k. Overall Comb. Length - 375 inches

4. BASE MODEL

- a. Model 389 - 15,007
- b. City Delivery - 0Truck or tractor which hauls frieght, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery.
- c. Winch or Crane - 0
- d. United States Registry - 0

5. CONFIGURATION

- a. Not Applicable - Secondary Manufacturer - 0

6. FRAME & EQUIPMENT

- a. 10-3/4in Steel Rails 355-384 in10.75x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair - 619
- b. Fuel Steel Inner Liner - 701

- c. Custom Wheelbase or Overhang - Engineering approval may be required.
- d. Three-Piece Crossmembers- 0
- e. Three-Piece Crossmembers - 0
- f. EOF Square without Xmbr - For use with body builder installed crossmember. - 0
- g. Omit Rear Mudflaps and Hangers - 0

7. FRONT AXLE & EQUIPMENT

- a. Dana Spicer D2000F 20,000lb, 3.5in Drop - Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins, & draglink ball joints for ease of maintenance & help extend service life of components. Cognis EMGARD FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life. - 445
- b. Taper Leaf Springs, Shocks 20,000lb (Standard with Heavy Resistance Shocks)- 0
- c. Power Steering Sheppard TRW THP60 Dual(For use with 16,000 to 20,000lb. axle ratings. Gildekote splines on steering shaft extend service life of components) - 0
- d. Power Steering Reservoir Frame Mounted with Cooler - 2
- e. PHP10 Iron PreSet PLUS Hubs - 0
- f. Bendix Air Cam Front Drum Brakes 16.5 x 6 - For use with 14,601 lbs to 22,000 lbs steer axles or FSD16 front drive axles. Includes automatic slack adjusters & outboard mounted brake drums. - 0
- g. Gusseted Cam Brackets, Steer Axle

8. REAR AXLE & EQUIPMENT

- a. Meritor MT44-14X 44,000lb Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.
- b. PHP10 Aluminum PreSet PLUS Hubs - 0
- c. Standard Stroke Parking Brakes - Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers. - 0
- d. Diff Lock Both Axles - (Air Rocker Switch occupies the space of one gauge) - 60
- e. Refuse Service Brakes, Steer and Drive Axles - 0
- f. Rear Brake Camshaft Reinforcement - 9
- g. SBM Valve - Full truck requires a spring brake modulation (SBM)system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system. - 0
- h. Stability System Not Selected or Not Available - 0
- i. Anti-Lock Braking System (ABS) 4S4M - ABS-6. Includes air braking system. - 0
- j. Synthetic Axle Lubricant All Axles - Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.-0
- k. Bendix Air Cam Rear Drum Brakes 16.5x7-Inc automatic slack adjusters & outboard mounted brake drums.-0
- l. Tandem Drive Axle (Model 348) - 0
- m. Ration 3.58 Rear Axle- 0
- n. Hendrickson Haulmax HMX460 46,000 lb, 54in Axle - Spacing, 60K Creep Rating - 593

9. ENGINE & EQUIPMENT

- a. PACCAR PX-9 380@1900 GOV@2100 1250@1400 -(2013 Emissions) Includes integrated engine retarder and return fuel blending valve. Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life. N21320 N205 120..Standard Maximum Speed Limit [LSL]N21330 N207 0...Expiration DistanceN21340 P005 120..Hard Maximum Speed LimitN21350 P001 69...Maximum Accelerator Pedal Vehicle SpeedN21360 P110 0...Accelerator Lower DroopN21370 P059 69...Maximum Cruise SpeedN21380 P111 0...Cruise Control Lower DroopN21400 N203 252..Reserve Speed Function Reset DistanceN21440 N202 0...Maximum Cycle DistanceN21420 N206 10...Maximum Active DistanceN21430 N201 0...Reserve Speed Limit OffsetN21440 P015 Yes...Engine Protection ShutdownN21450 P026 NO...Gear Down ProtectionN21460 P046 1400.Max PTO SpeedN21470 P062 No....Cruise Control Auto ResumeN21480 P068 NO...Auto Engine Brake in CruiseN21500 N209

- 0....Expiration DistanceN21510 P520 Yes..Enable Idle Shutdown Park Brake SetN21520 P030 5....Timer SettingN21530 P233 Yes..Enable Impending Shutdown WarningN21540 P234 60...Timer fro Impending ShutdownN21550 P516 35...Engine Load ThresholdN21570 P031 No...Idle Shutdown Manual OverrideN21590 P230 Yes..Enable Hot Ambient Automatic OverrideN21610 P172 40...Low Ambient Temperature ThresholdN21620 P173 60...Intermediate Ambient Temperature ThresholdN21630 P171 80...High Ambient Temperature Threshold
- b. Engine Idle Shutdown Timer Enabled - 0
 - c. Enable EIST Ambient Temp Override - 0
 - d. Eff EIST NA Expiration Miles - 0
 - e. Enable VSL Setting NA -0
 - f. CARB Engine Idling Compliance DECLINED By - Dealer/Customer - 0
 - g. PACCAR 160 Amp Alternator, Brushed - 0
 - h. Immersion Type Block Heater 110-120V - Standard location is center left hand under cab and includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running. - 2
 - i. PACCAR 12V Starter - 0
 - j. 2 PACCAR Premium 12V Starting Batteries 2000 CCA - Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance. - 0
 - k. 2-Speed Fan Clutch for Frequent Start/Stops - 0
 - l. 18.7 CFM Air Compressor - Furnished on engine. Teflon lined stainless steel braided compressor discharge line. - 0
 - m. C-Brake By Jacobs, PX-9 - 90
 - n. Spin-on Fuel Filter/Water Separator, Unheated - Frame Mounted. In addition to the fuel filter supplied with the engine. - 0
 - o. High Efficiency Cooling System - Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Climax Tech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective 10 -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEOTIL 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in - 0
 - p. Radial Seal, Dry Type Air Cleaner, Frontal - Air intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake. - 0

10. TRANSMISSION & EQUIPMENT

- a. Allison 4500 RDS-P Transmission, Gen 5Rugged Duty Series. Includes Rear Transmission Support, TranSynd Transmission Fluid, and Water Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. (Suited for vehicles operating on/off highway and/or requiring PTO operation) Forward Ratios: 1st-4.70, 2nd-2.21, 3rd-1.53, 4th-1.00, 5th-0.76, 6th-0.67/Reverse Ratios: DR-(5.55)- 475
- b. 1760 HD Driveline, 2 Midship Bearings - 80
- c. (1) Dash Mounted Single Acting Air PTO Control - Standard with PTO engaged indicator light on Class 8 units. Occupies the space of one gauge. - 0
- d. Allison 5th Gen RDS, Pkg 223 - 0
- e. Allison FuelSense Not Desired - 0
- f. Allison 6-Speed Configuration, Wide Ratio Gears - Allison 4500 Transmission Only - 0
- g. Dash Mounted Push Button Shifter - 0

11. AIR & TRAILER EQUIPMENT

- a. Bendix AD-IS Air Dryer with Heater - An integrated system air dryer that incorporates the functions of the air dryer, purge reservoir(which increases the drying capacity), wet air tank, pressure relief valve, single check valves, and pressure protection valve for air susp and other air accessories. Includes easy-to-service spin-on dessicant cartridge. - 39
- b. Nylon Chassis Hose - 0
- c. Steel Painted Air Tanks - All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rials will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed. - 0
- d. Body Connections 5ft BOC - Junction Box contains light and power circuits for Body Connections located 5ft from BOC - 4
- e. Berg Pull Cord Drain Valve(s) - All Air Tanks - 0

f. A&E Conn EOF w/7-way Socket (w/Conn EOF Strapped to the rail) - 15

12. TIRES & WHEELS

- a. FF: Accur Stl Amor 29039PK 22.5*9.00 PHP 10-5 Hand Holes - 68RR: Accur Steel Armor 29300PK 22.5x9.00 PHP 10-5 Hand holes - 164Code-rear Rim Qty 08 - 0NO TIRE CHAINS DUE TO TIRE/SUSP CLEAR

13. FUEL TANKS

- a. 23in Aluminum 100 Gallon Fuel Tank RH U/C - SBFA requires high mount, horizontal, or through-the-rails exhaust. Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability and reduce potential for leaks - 20
- b. Location RH BOC 100 Gallon - 0
- c. Standard DEF to Fuel Ratio 2:1 or Greater - 0
- d. DEF Tank Small - 0
- e. DEF Tank Mounted RH BOC - You have selected a Diesel Exhaust Fluid (DEF) tank mounted on the right-hand (passenger) side of the vehicle. Note, some retail fuel distributors have chosen to standardize on DEF dispensing pumps oriented to the left-hand (driver) side of the vehicle. Please verify your selection for DEF tank mounting. - 0

14. BATTERY BOX & BUMPER

- a. Rubber Battery Pad in Bottom Of (1) Battery Box - (Mat in box that holds batteries only) - 2

15. CAB & EQUIPMENT

- a. Alum Cab 110in BBC Metton Hood - With bright finish crown. Includes view window RH door and convex mirror over RH door. - 0
- b. Serve Service Cab Package #1 - Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab. - 39
- c. Thermal Insulation Package in Cab - Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure. - 2
- d. Rubber Fender Lips 2 Inch Wide - 8
- e. Peterbilt UltraRide Drive Seat - 0
- f. Peterbilt UltrRide Passenger Seat - 0
- g. Drivers Armrests - LH & RH - Required in Model 587 with Evolution LX seats, optional with Evolution ST and Rolltek Seats. - 4
- h. Non-Air Ride Passenger - 0
- i. High Back Passenger - 0
- j. Air Ride Drive - 0
- k. High Back Driver - 0
- l. Mordura Passenger - 0
- m. Manifest Pouch on Rear Cab Wall - 0
- n. Adjustable Steering Column - Tilt/Telescope - 11
- o. Steering Wheel with Peterbilt Logo - Steering Wheel with embossed Peterbilt logo over horn button. - 0
- p. Interior Grey/Black - Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2)cup holders and map bin in dash. - 0
- q. Extended Rear Window ipo Std Window-Day Cab - The extended rear window protrudes two inches more than the standard conventional rear cab window. Take this into consideration when determining your loadspace. - 0
- r. Day Cab Rear Window - 0
- s. One Piece Curved Windshield - 0
- t. Combo Fresh Air Heater/Air Conditioner - With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses - 0
- u. Outside Sunvisor - Stainless Steel - Not available with 2.1M high roof sleeper. - 4
- v. Stainless Steel Mirrors 7x16 with Heat Element - Right Click on Option to see Picture in Product Portfolio - 2
- w. (2) Convex 8 Inch SS Mirror - Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops - 4
- x. Polished Lower Mirror Bracket Covers - 0
- y. (1) Air Horn 24.5in Chrome - Round w/Horn Shield
- a`. Standard Speak Package for Cab - (2) Speakers - 4

- aa. ConcertClass Without CD, Includes BT Phone and - Audio, AM/FM, WB, USB and MP3 - 10
- ab. Plug-In Auto Reset Circuit Breaker - in place of fuses in junction box - 0
- ac. Peterbilt Electric Windshield Wipers - With Intermittent Feature - 0
- ad. Unibilt Cab Air Suspension - Includes dual air bag suspension, leveling valve, and tracking rod. - 25
- ae. Triangle Reflector Kit Shipped Loose - 13
- af. Backup Alarm (107dB) - 3
- ag. Air Restriction Indicator - Mounted on air cleaner or intake piping - 0
- ah. Bright Bezel Gauges - 0
- ai. Main Instruction Panel, Graphics Display - Includes speedometer with tripodometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights w/audible alarms, high beam, turn signal, low fuel, parking brake, and ice indicators; multi-function turn stalk with flas-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges. - 0
- aj. Headlights Composite Fender Mounted - Integral Park, Turn, and Side marker - 0
- ak. (5) Marker Lights, Aero LED - Light Emitting Diodes - 0
- al. (2) Addl Dome/Reading Lights, Ceiling Mounted - 0

16. OPTIONS NOT SUBJECT TO DISCOUNT

- a. Heavy Duty Emissions Surcharge - 0

17. MISCELLANEOUS

- a. Day Cab/ProBilt Interior (DB) - 0
- b. Presentation Created Using Featured Sepc - For Model - 0

18. BODY

- a. Type: Roll-Off
- b. Length (ft): 24
- c. Height (ft): 8.5
- d. Max Laden Weight (lbs): 1000

19. PAINT

- a. Standard Paint Selection - 0
- b. (1) Color Axalta Two Stage - Cab/HoodBase Coat/Clear CoatN85020 A - L0006EB WHITE - StandN85400
HOODTOP L0006EB WHITE - StandN85500 CAB ROOF L0006EB WHITE - StandN85200 FRAME N0001EA
BLACKN85300 FENDER L0006EB WHITE - Stand - 0



NORTH CAROLINA SHERIFFS' ASSOCIATION

PETERBILT - MODEL 348 ROLL-OFF SPECIFICATION #49

2017 Peterbilt Model 348

The Peterbilt Model 348 purchased through this contract comes with all the standard equipment as specified by the manufacturer for this model and NCSA's base vehicle specification(s) requirements which are included and made a part of this contract's vehicle base price as awarded by specification by zone.

ZONE:	★Appalachia	★Dogwood	★Cardinal	★Longleaf Pine
BASE PRICE:	\$110,205.00	\$110,205.00	\$110,205.00	\$110,205.00

While the North Carolina Sheriffs' Association has attempted to identify and include those equipment items most often requested by participating agencies for full size vehicles, we realize equipment needs and preferences are going to vary from agency to agency. In an effort to incorporate flexibility into our program, we have created specific add/delete options which allow the purchaser to tailor the vehicle to their particular wants or needs.

The following equipment delete and add options and their related cost are provided here to assist you in approximating the total cost of the type vehicle(s) you wish to order through this program. Simply deduct the cost of any of the following equipment items you wish deleted from the base unit cost and/or add the cost of any equipment items you wish added to the base unit cost to determine the approximate cost of the type vehicle(s) you wish to order.

NOTE: An official listing of all add/delete options and their prices should be obtained from the appropriate dealer in your zone when preparing your order. Additional add/delete options other than those listed here may be available through the dealers, however, those listed here must be honored by the dealers in your zone at the stated prices.

VEHICLE:	Model 348			
DEALER:	Peterbilt of Knoxville	Peterbilt of Knoxville	Peterbilt of Knoxville	Peterbilt of Knoxville
ZONE:	★ Appalachia	★ Dogwood	★ Cardinal	★ Longleaf Pine
BASE PRICE:	\$110,205.00	\$110,205.00	\$110,205.00	\$110,205.00

Order Code	Delete Options	All Zones
	Aluminum Battery Box LH Under Cab, Non-Slip Step - Includes diamond pattern block shaped cover in traditional/vocational models and a smooth finish tapered cover on aerodynamic models -55	Incl.
	Tow Tow Pins	Std

Order Code	Add Options	All Zones
	Aluminum	Std
	Metton 108" BBC	Std
	44", 58" & 72" Low Roof	NA
	58", 72" & 78" Ultra Cab	NA
	Driver: Peterbilt UltraRide	Std
	Passenger: Peterbilt UltraRide or 2-Person <i>2 person</i> ¹	\$351.00 ¹
	PACCAR PX-9, 260-380 HP <i>260 px 9</i> ¹	Std ¹
	PACCAR PX-7, 280-360 HP <i>300 px7</i> ¹	(\$2,300.00) ¹
	Under Hood	Std
	Vertical Cab Mounted or Horizontal <i>rh cab mounted vert</i> ¹	Std ¹
	Stainless Steel (Vertical)	Incl.
	Fuller 6 Speed Manual	NA
	Fuller 9 Speed Manual	(\$18,000.00)
	Fuller 10 Speed Manual	(\$17,000.00)
	Fuller 11 Speed Manual	(\$16,000.00)
	Allison 6-Speed Automatic <i>4500 rdsp 6 speed</i> ¹	Incl. ¹
	10 5/8", 10 3/4', 11 5/8" <i>10/34</i> ¹	Incl. ¹
	12,000 lbs.	(\$1,500.00)
	13,000 lbs	(\$1,200.00)
	14,000 lbs	(\$750.00)
	14,600 lbs	(\$561.00)
	Taper Leaf	Incl.
	Iron LMS or Aluminum LMS - Non Driving, Iron Front Driving Axle <i>iron hubs</i> ¹	Incl. ¹
	Air Disc or Air Cam Drum <i>cam front</i> ¹	Incl. ¹

VEHICLE:	Model 348			
DEALER:	Peterbilt of Knoxville	Peterbilt of Knoxville	Peterbilt of Knoxville	Peterbilt of Knoxville
ZONE:	★ Appalachia	★ Dogwood	★ Cardinal	★ Longleaf Pine
BASE PRICE:	\$110,205.00	\$110,205.00	\$110,205.00	\$110,205.00

Dana Spicer (21,000 lbs, 23,000 lbs, 25,000 lbs, 26,000 lbs, 30,000 lbs)	NA
Meritor (40,000 lbs, 44,000 lbs) <i>44000 meritor</i> ¹	Incl. ¹
40,000 lbs	(\$300.00)
44,000 lbs	Incl.
46,000 lbs	\$1,000.00
Iron or Aluminum Pre-Set Plus	Incl.
Air Disc or Air Cam Drum <i>air disc rear</i> ¹	\$4,043.00 ¹
Bendix 4S4M or 6S6M Air <i>6sms</i> ¹	\$338.00 ¹
20,000 lbs	NA
23,000 lbs	NA
26,000 lbs	NA
31,000 lbs	NA
Peterbilt Air Trac	(\$650.00)
Peterbilt Low Air Leaf	(\$2,200.00)
Hendrickson RT	(\$700.00)
HMX	Incl.
Reyco	(\$2,800.00)
Chalmers 854	\$1,000.00
Bridgestone, Goodyear or Michelin <i>bridgestone tires on vehicle</i> ¹	Incl. ¹
Steel or Aluminum (22.5", 24,5")	Incl.
Black Molded Stainless Steel	\$105.00
Holland or Jost	NA
Bendix	Incl.
Steel or Aluminum <i>steel</i> ¹	Std ¹
Nylon	NC
Optional <i>air and electric to rear</i> ¹	Incl. ¹
23" Aluminum (50-120 Gallon)	Incl.
26" Aluminum (50-120 Gallon) <i>26 in 100 gallon</i> ¹	\$194.00 ¹
Steel 45 Gallon	Std
Aluminum or Steel <i>aluminum</i> ¹	Incl. ¹

VEHICLE:	Model 348			
DEALER:	Peterbilt of Knoxville	Peterbilt of Knoxville	Peterbilt of Knoxville	Peterbilt of Knoxville
ZONE:	★ Appalachia	★ Dogwood	★ Cardinal	★ Longleaf Pine
BASE PRICE:	\$110,205.00	\$110,205.00	\$110,205.00	\$110,205.00

	Optional <i>dealer add</i> ¹	\$200.00 ¹
	Steel Stylized Aerodynamic, Aluminum Swept Back or Aluminum Channel <i>aluminum stainless steel</i> ¹	Incl. ¹
	0	Incl.
	DPF/SCR series under frame. - -99	(\$800.00)