



NORTH CAROLINA SHERIFFS' ASSOCIATION

Name of Dealership	Type of Vehicle	Zone	Base Unit Price
<u>PETERBILT - MODEL 567 END DUMP (Specification #53)</u>			
Peterbilt of Charlotte	2017 Peterbilt End Dump - Model 567	★Appalachia	\$128,477.00
Peterbilt of Charlotte	2017 Peterbilt End Dump - Model 567	★Dogwood	\$128,477.00
Peterbilt of Charlotte	2017 Peterbilt End Dump - Model 567	★Cardinal	\$128,477.00
Peterbilt of Charlotte	2017 Peterbilt End Dump - Model 567	★Longleaf Pine	\$128,477.00



NORTH CAROLINA SHERIFFS' ASSOCIATION

PETERBILT - MODEL 567 END DUMP **SPECIFICATION #53**

2017 Peterbilt End Dump - Model 567

ALL ITEMS FACTORY INSTALLED UNLESS OTHERWISE INDICATED

INSTRUCTIONS: Listed above, you will find the model numbers of the vehicles that will be included in this year's contract.

1. BASE MODEL

- a. End Dump - 0
- b. City Delivery - Truck or tractor which hauls freight, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery. - 0
- c. Construction Materials - 0
- d. Model 567 - 15,219
- e. United States Registry - 0

2. RESTRICTIONS

- a. Height 13.5 feet
- b. Width 102 inches
- c. Length 40 feet

3. CHASSIS

- a. Overall Comb. Length - 298 inches
- b. Cab to EOF - 182.8 inches
- c. Cab to Axle - 127.8 inches
- d. Fr Axle to BOC - 86.2
- e. Overhang - 55 inches
- f. Wheelbase - 214 inches
- g. Maximum Grade - 6
- h. Road Conditions - Class A (Highway)- 100Class B (Hwy/Mtn) - 0Class C (Off-Hwy) - 0Class D (Off-Road) - 0
- i. G.C.W. - 66000 lbs
- j. Fr Axle Load - 46000 lbs
- k. Fr Axle Load - 20000 lbs

4. CONFIGURATION

- a. Not Applicable - Secondary Manufacturer - 0

5. FRAME & EQUIPMENT

- a. EOF Square with Steel Xmbr - 0
- b. Aluminum Frame Rail Crossmembers - 0
- c. Heavy-Duty Iron Front Spring Brackets - Forward/Rear - 35
- d. Fuel Steel Inner Liner - 597
- e. 10-3/4in Steel Rails to 354in - 10.75x3.5x375 Dimension, 2,136,000 RBM; Yield Strength: 120,000psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair - 232
- f. Peterbilt Rear Mudflaps and Straight Hangers -0

6. FRONT AXLE & EQUIPMENT

- a. Dana Spicer D2000F 20,000lb, 3.5in Drop - Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins, & draglink ball joints for ease of maintenance & help extend service life of components. Cognis EMGARD FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life. - 445
- b. Taper Leaf Springs, Shocks 20,000lb (Standard with Heavy Resistance Shocks)- 175
- c. Power Steering Sheppard SD 110 Dual(For use with 22,000lb. axle ratings. Gildekote splines on steering shaft extend service life of components) - 0
- d. Power Steering Reservoir Frame Mounted with Cooler - 2
- e. Bendix Air Cam Front Drum Brakes 16.5x6 -For use with 14,601 lbs to 22,000 lbs steer axles or FSD16 front drive axles. Includes automatic slack adjusters & outboard mounted brake drums. - 0
- f. Gusseted Cam Brackets, Steer Axle

7. REAR AXLE & EQUIPMENT

- a. Dana Spicer D46-170 46,000 - Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.
- b. Watson-Chalin SL 1190SSR (1) 13,500 lb Pusher - Includes (1) air tank. Self-Steering Pusher - 945
- c. 48in Pusher Axle Spacing - From Centerline of Forward Drive Axle. - 0
- d. PH10 Iron PreSet PLUS Hubs, Cast Drums - Self-Steering Pusher Axles - 0
- e. Anti-Lock Braking System (ABS) 6S6M - ABS-6. Includes air braking system. - 0
- f. Synthetic Axle Lubricant All Axles - Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.-0
- g. Bendix Air Cam Rear Drum Brakes 16.5x7 - Inc automatic slack adjusters & outboard mounted brake drums - 0
- h. Ratio 3.58 Rear Axle- 0
- i. Hendrickson Haulmaax HMX460 46,000 lb, 54in Axle - Spacing, 60K Creep Rating - 276
- j. Stability System Not Selected or Not Available - 0
- k. PHP10 Aluminum PreSet PLUS Hubs - 0
- l. Long Stroke Parking Brakes, Drive Axle(s)-0
- m. Rear Brake Camshaft Reinforcement - 9
- n. Gusseted Cam Brackets, Drive Axle(s) - 2
- o. SBM Valve - Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.

8. ENGINE & EQUIPMENT

- a. PACCAR PX-9 380@1900 GOV@2100 1250@1400 -(2013 Emissions) Includes integrated engine retarder and return fuel blending valve. Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life. N21320 N205 120..Standard Maximum Speed Limit [LSL]N21330 N207 0...Expiration DistanceN21340 P005 120..Hard Maximum Speed LimitN21350 P001 69...Maximum Accelerator Pedal Vehicle SpeedN21360 P110 0...Accelerator Lower DroopN21370 P059 69...Maximum Cruise SpeedN21380 P111 0...Cruise Control Lower DroopN21400 N203 252..Reserve Speed Function Reset DistanceN21440 N202 0...Maximum Cycle DistanceN21420 N206 10...Maximum Active DistanceN21430 N201 0...Reserve Speed Limit OffsetN21440 P015 Yes...Engine Protection ShutdownN21450 P026 NO...Gear Down ProtectionN21460 P046 1400.Max PTO SpeedN21470 P062 No...Cruise Control Auto ResumeN21480 P068 NO...Auto Engine Brake in CruiseN21500 N209 0...Expiration DistanceN21510 P520 Yes..Enable Idle Shutdown Park Brake SetN21520 P030 5....Timer SettingN21530 P233 Yes..Enable Impending Shutdown WarningN21540 P234 60...Timer fro Impending ShutdownN21550 P516 35...Engine Load ThresholdN21570 P031 No...Idle Shutdown Manual OverruleN21590 P230 Yes..Enable Hot Ambient Automatic OverruleN21610 P172 40...Low Ambient Temperature ThresholdN21620 P173 60...Intermediate Ambient Temperature ThresholdN21630 P171 80...High Ambient Temperature Threshold
- b. Engine Idle Shutdown Timer Enabled - 0
- c. Enable EIST Ambient Temp Overrule - 0
- d. Eff EIST NA Expiration Miles - 0

- e. Enable VSL Setting NA - 0
- f. CARB Engine Idling Compliance DECLINED By - Dealer/Customer - 0
- g. PACCAR 160 Amp Alternator, Brushed - 0
- h. PACCAR Fuel Filter/Water Separator, Unheated - With water in fuel (WIF) sensor. In addition to the fuel filter supplied with the engine.
- i. PACCAR 12V Starter - 0
- j. 3 PACCAR Premium 12V Starting Batteries 2100 CCA - Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance. - 0
- k. 2-Speed Fan Clutch for Frequent Start/Stops - 0
 - l. 18.7 CFM Air Compressor - Furnished on engine. Teflon lined stainless steel braided compressor discharge line. - 0
- m. C-Brake By Jacobs, ISX12, ISX12-G - 0
- n. (1) Air Cleaner Firewall Mounted - Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake. - 0
- o. High Efficiency Cooling System - Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Climax Tech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective 10 -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEOTIL 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in - 0
- p. Exhaust Single RH Side of Cab - DPF/SCR RH under cab. Includes cab entry RH under cab and full round stainless steel exhaust guard - 0
- q. Curved Tip Standpipe(s) - 0
- r. 24in Ht, 5ib Dia Chrome, Clear Coat Standpipe(s) - 0

9. TRANSMISSION & EQUIPMENT

- a. Allison 4500 RDS-P Transmission, Gen 5 - Rugged Duty Series. Includes Rear Transmission Support, TranSynd Transmission Fluid, and Water Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. (Suited for vehicles operating on/off highway and/or requiring PTO operation) Forward Ratios: 1st-4.70, 2nd-2.21, 3rd-1.53, 4th-1.00, 5th-0.76, 6th-0.67/Reverse Ratios: DR-(5.55)- 245
- b. 1810 HD Driveline, 1 Midship Bearings -105
- c. 1710 Driveline Interaxle, Tandem Rear Axles - 0
- d. Allison FuelSense Basic - Includes 5th Generation Controls, EcoCal and Dynamic Shift Sensing. For additional information see Product Portfolio - 0
- e. Allison 6-Speed Configuration, Wide Ratio Gears - Allison 4500 Transmission Only - 0
- f. Dash Mounted Lever Shifter- N/A with manual transmissions - 8

10. AIR & TRAILER EQUIPMENT

- a. Bendix AD-IS Air Dryer with Heater - Extended Purge (for use with higher air consumption applications). An integrated system air dryer that incorporates the functions of the air dryer, purge reservoir (which increases the drying capacity), wet air tank, pressure relief valve, single check valves, and pressure protection valve for air susp and other air accessories. Includes easy-to-service spin-on dessicant cartridge- 4
- b. Nylon Chassis Hose - 0
- c. Steel Painted Air Tanks - All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed. - 0
- d. Berg Pull Cord Drain Valve(s) - All Air Tanks - 0

11. TIRES & WHEELS

- a. FF: BR 20ply 315/80R22.5 M860A Diameter+ 42.8 inches; SLR= 19.9 inches - 102RR: BR 14ply 11R22.5 R268 Ecopia Diameter=41.5 inches; SLR=19.3 inches - 64
- b. Code-rear Tire Qty 08 - 0Code-rear Rim Qty 08 - 0TP: (2) BR 18ply 275/70R22.5 R250ED - For single self-steering tag/pusher axles; Diameter=38.0 inches; SLR=17.6 inches - 220TP: (1) Alcoa 885657 LvL1 PLT 22.5x8.25 - Aluminum Wheel, Severe Service, Steerable T/P Axle - 100

12. FUEL TANKS

- a. Location LH U/C 100 Gallon - 0
- b. Standard DEF to Fuel Ratio 2:1 or Greater - 0
- c. DEF Tank Mounted LH BOC - Models 210,220 and 320 mounted LH cab fender - 0
- d. DEF Tank Small - 0

13. BATTERY BOX & BUMPER

- a. Aftertreatment RH U/C Alum Non-Slip Cab Entry - Step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box will be aerodynamic. - 0
- b. Steel Bumper Tapered Chromed - Two tow pins. - 19

14. CAB & EQUIPMENT

- a. Serve Service Cab Package #1 - Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab. - 39
- b. Peterbilt ST Driver - Peterbilt ST air seat, high height backrest, adjustable seat track length, 1 chamber lumbar support, suspension with fixed damping, fore-aft isolator with lockout, Vinyl bellows over suspension. Standard vinyl finish - color coordinate with interior color - 0
- c. Rubber Fender Lips 4.5 Inches Wide - 6
- d. Peterbilt ST Passenger seat - Peterbilt ST air seat, high height backrest, adjustable seat track length, 1 chamber lumbar support, suspension with fixed damping, fore-aft isolator with lockout, Vinyl bellows over suspension. Standard vinyl finish - color coordinate with interior color - 0
- e. Air Ride Drive - 0
- f. High Back Passenger - 0
- g. Vinyl Driver - 0
- h. High Back Driver - 0
- i. Air Ride Passenger - 43
- j. Vinyl Passenger - 0
- k. Steering Wheel with Peterbilt Logo - Steering Wheel with embossed Peterbilt logo over horn button. - 0
- l. Adjustable Steering Column - Tilt/Telescope - 10
- m. Prestige Interior Titanium - Includes innovative gun metal A,B&C instrument panels and color-matched D instrument panel, monochromatic color-coordinated dash with glare-resistant, soft-touch upper, power ports, burlwood insert on contoured doorpads, LH and RH door mounted map pockets with built-in courtesy lights, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift driver and passenger windows, padded fabric headliner and vinyl wall panels, extruded rubber floor covering, (3) inside sunvisors, (2) coat hooks, header-mounted dome light, driver and passenger dome/reading lights, footwell lighting, integrated "dead pedal", (4) inside entry grab handles, cup holder and map bin in dash. REQUIRES black bezel on gauges.
- n. 1-Piece Glass Rear Cab Window Fixed - 0
- o. Cup Holder (Floor Mounted) - Includes two standard-size drink holders and one extra-large jugholder, coin tray and clipboard-size storage area. - 4
- p. Day Cab Rear Window - 0
- q. One Piece Curved Windshield - 0
- r. Combo Fresh Air Heater/Air Conditioner - With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses - 0
- s. Outside Sunvisor - Stainless Steel - Not available with 2.1M high roof sleeper. - 8
- t. Power Door Locks AND Power Window Lifts - Standard - 0
- u. Peterbilt Aero Rear View Mirror, Motorized - Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature - 3
- v. Aero Rear View Mirror Housing - body Color - 0
- w. Air Horn Mounted Under Cab - 0
- x. Standard Speak Package for Cab - (2) Speakers - 4
- y. ConcertClass Without CD, Includes BT Phone and - Audio, AM/FM, WB, USB and MP3 - 10
- a. Look Down Mirror Over Passenger Door - with Black Housing - 0
- aa. CB Terminal Wiring, Microphone Clip, Speaker - F/O CB radio mounted center of header. Select antenna separately - 3
- ab. (1) Antenna For Factory Installed or F/O CB - Mounted LH side of roof, with antenna cable. - 5
- ac. Peterbilt Electric Windshield Wipers - with Intermittent Feature - 0
- ad. Cab Air Suspension - 15
- ae. 5lb Dry Chemical ABC Fire Extinguisher- Mounted with metal strap outboard of driver seat. - 8
- af. Backup Alarm (107dB) - 3
- ag. Main Instruction Panel - Includes Driver Information Display and Instrument Package with Speedometer, Tachometer, Fuel Level Gauge, Engine Oil Pressure, Engine Coolant temperature, (2) Air Pressure, DEF Level Gauge.

- With Gas Engines, DEF Level Gauge will be replaced with Brake Application Gauge - 0
- ah. Headlights Projector Module Pod - Fender Mounted turn signals. Projector Module Low Beam, Complex Reflector High Beam. Pod Mounted - 0
 - ai. Main Transmission Oil Temperature Gauge - Located in Driver Information Display - 0
 - aj. Engine Oil Temperature Gauge - 52mm round, backlit. These physical gauges must be ordered in pairs and are limited to a total of 6- 0
 - ak. Air Filter Restriction Pressure Gauge - Located in Driver Information Display - 0
 - al. Pusher Axle Pressure 1 - 52mm round and backlit. These physical gauges must be ordered in pairs and are limited to a total of 6. - 0
 - am. (2) Peterbilt Fog Lights - Recessed in bumper - 6
 - an. Daytime Running Lights - (Required on Canadian units) - 0
 - ao. (5) Marker Lights, Aero LED - On roof, visor or fairing - 0
 - ap. LED Stop/Turn/Tail - 40204 Backup, bracket mounted LH/RH EOF - 2
 - aq. Peterbilt Signature Door Light Turn Signal - 0

15. OPTIONS NOT SUBJECT TO DISCOUNT

- a. Cummins 2013 ISX Protection Plan 1 (5/300)- ISX15 or ISX12=< 475HP. Five Years/300,000 Miles/482,804 Kilometers. Coverage is 100 percent parts and labor with not deductibles on internally lubricated components and major engine systems including turbo charger, water pump, and fuel injectors - 0
- b. Cummins 2013 ISX Protection Plan 1 (5/300)- ISX15 or ISX12=< 475HP. Five Years/300,000 Miles/482,804 Kilometers. Coverage is 100 percent parts and labor with not deductibles on the DEF controller/dosing unit/dosing valve, SCR catalyst, catalytic converter particulate filter, SCR/DPF temperature sensor interface module, and other related aftertreatment parts as detailed in Cummins Bulletin #3381446 - 0
- c. Heavy Duty Emissions Surcharge - 0

16. MISCELLANEOUS

- a. Day Cab/ProBilt Interior (DB) - 0
- b. Presentation Created Using Featured Sepec - For Model - 0

17. BODY

- a. Type: Roll-Off
- b. Length (ft): 24
- c. Height (ft): 8.5
- d. Max Laden Weight (lbs): 1000

18. PAINT

- a. Standard Paint Selection - 0
- b. (1) Color Axalta Two Stage - Cab/HoodBase Base Coat/Clear Coat CoatN85020 A - L0006EY WHITE - StandN85400 HOODTOP L0006EY WHITE - StandN85500 CAB ROOF L0006EY WHITE - StandN85200 FRAME N0001EA BLACKN85300 FENDER L0006EY WHITE - Stand - 0

19. MISCELLANEOUS

- a. Day Cab/Prestige Interior (DM) - 0
- b. Presentation Created Using Featured Spec - for Model - 0



NORTH CAROLINA SHERIFFS' ASSOCIATION

PETERBILT - MODEL 567 END DUMP SPECIFICATION #53

2017 Peterbilt End Dump - Model 567

The Peterbilt End Dump - Model 567 purchased through this contract comes with all the standard equipment as specified by the manufacturer for this model and NCSA's base vehicle specification(s) requirements which are included and made a part of this contract's vehicle base price as awarded by specification by zone.

ZONE:	★Appalachia	★Dogwood	★Cardinal	★Longleaf Pine
BASE PRICE:	\$128,477.00	\$128,477.00	\$128,477.00	\$128,477.00

While the North Carolina Sheriffs' Association has attempted to identify and include those equipment items most often requested by participating agencies for full size vehicles, we realize equipment needs and preferences are going to vary from agency to agency. In an effort to incorporate flexibility into our program, we have created specific add/delete options which allow the purchaser to tailor the vehicle to their particular wants or needs.

The following equipment delete and add options and their related cost are provided here to assist you in approximating the total cost of the type vehicle(s) you wish to order through this program. Simply deduct the cost of any of the following equipment items you wish deleted from the base unit cost and/or add the cost of any equipment items you wish added to the base unit cost to determine the approximate cost of the type vehicle(s) you wish to order.

NOTE: An official listing of all add/delete options and their prices should be obtained from the appropriate dealer in your zone when preparing your order. Additional add/delete options other than those listed here may be available through the dealers, however, those listed here must be honored by the dealers in your zone at the stated prices.

VEHICLE:	End Dump - Model 567			
DEALER:	Peterbilt of Charlotte	Peterbilt of Charlotte	Peterbilt of Charlotte	Peterbilt of Charlotte
ZONE:	★Appalachia	★Dogwood	★Cardinal	★Longleaf Pine
BASE PRICE:	\$128,477.00	\$128,477.00	\$128,477.00	\$128,477.00

Order Code	Delete Options	All Zones
	Aluminum Battery Box LH Under Cab, Non-Slip Step - Includes diamond pattern block shaped cover in traditional/vocational models and a smooth finish tapered cover on aerodynamic models -55	
	Tow Tow Pins	
	Omit Standard Trailer Connection Package - (Omits 12ft A&E linfes, Hose Tenna, and Hand Valve) - -28	
	FF: Alcoa 893657 LVL1 22.5x9.00 Alum Wheel- Pilot Mount -38	
	RR: Alcoa 883677 LvL1 22.5x8.25 Alm Wheel -200	
	Aluminum Space Saver Battery Box RH BOC - Battery Access From Side - -60	
	RH Tank None Furnished - -86	
	Vocational 115 BBC Alum Cab and Metton Hood SFFA - Stainless steel crown and grille with tilt assist. - -210	

Order Code	Add Options	All Zones
	Aluminum	
	Metton 108" BBC	
	44" (Low Roof), 58" (Low Roof or Mid Roof), 72" or 80"	
	Driver: Peterbilt Evolution ST or Lx	
	Passenger: Peterbilt Evolution ST or LX	
	PACCAR MX-13	
	PACCAR PX-9	
	Cummins ISX12	
	Cummins ISX15	
	Single Under Hood	
	Single (Horizontal, Vertical)	
	Dual (Vertical)	
	Stainless Steel (Vertical)	
	Fuller 9, 10, 11, 13, 15 or 18-Speed Manual	
	Fuller 10, 11, 13 or 18-Speed Automatic	
	Allison 4, 5 or 6-Speed Automatic	
	10 5/8", 10 3/4', 11 5/8" or 13 3/8" Steel	
	Dana Spicer (12,000 lbs., 13,200 lbs., 14, 600 lbs., 20,000 lbs)	
	Meritor (12,000lbs, 20,000lbs)	
	Taper Leaf	
	Iron or Aluminum Pre-Set Plus	
	Air Disc or Air Cam Drum	

VEHICLE:	End Dump - Model 567			
DEALER:	Peterbilt of Charlotte	Peterbilt of Charlotte	Peterbilt of Charlotte	Peterbilt of Charlotte
ZONE:	★ Appalachia	★ Dogwood	★ Cardinal	★ Longleaf Pine
BASE PRICE:	\$128,477.00	\$128,477.00	\$128,477.00	\$128,477.00

	Dana Spicer (21,000 lbs, 23,000 lbs, 25,000 lbs, 26,000 lbs, 30,000 lbs)	
	Meritor (40,000 lbs, 44,000 lbs)	
	Dana Spicer (40,000 lbs, 46,000 lbs, 52,000 lbs)	
	Meritor (40,000 lbs, 44,000 lbs, 46,000 lbs)	
	Iron or Aluminum Pre-Set Plus	
	Air Disc or Air Cam Drum	
	Bendix 4S4M or 6S6M Air	
	Peterbilt AirTrac	
	Reyco 79KB, 102 or 102AR	
	Peterbilt Air Trac	
	Peterbilt Air Leaf	
	Hendrickson HMX or RT	
	Chalmers 854	
	Reyco 102	
	Neway ADZ	
	Peterbilt Low air Leaf	
	Peterbilt FlexAir	
	Bridgestone, Goodyear or Michelin	
	Steel or Aluminum (22.5", 24,5")	
	Black Molded Stainless Steel	
	Holland or Jost	
	Bendix	
	Steel or Aluminum	
	Nylon or Wire Braid	
	Back of Cab or End of Frame	
	20" Aluminum (50-0 Gallon)	
	23" Aluminum (50-120 Gallon)	
	26" Aluminum (50-150 Gallon)	
	Aluminum	
	Aluminum	
	Steel Painted or Chrome, Aluminum, Natural or Polished	
	0	
	DPF/SCR series under frame. - -99	
	Air Disc or Air Cam Drum	
	Dana Spicer (21,000 lbs, 23,000 lbs, 25,000 lbs, 26,000lbs, 30,000lbs)	
	Meritor (21,000 lbs, 23,000 lbs)	
	Dana Spicer (40,000lbs, 44,000lbs, 46,000lbs, 52,000lbs)	

VEHICLE:	End Dump - Model 567			
DEALER:	Peterbilt of Charlotte	Peterbilt of Charlotte	Peterbilt of Charlotte	Peterbilt of Charlotte
ZONE:	★Appalachia	★Dogwood	★Cardinal	★Longleaf Pine
BASE PRICE:	\$128,477.00	\$128,477.00	\$128,477.00	\$128,477.00

Meritor (40,000lbs, 44,000lbs, 46,000lbs)	
Dana Spicer 69,000 lbs	
Meritor 66,000 lbs	
Peterbilt Air Trac	
Neway ADZ	